

1A, 20V - 150V Schottky Barrier Surface Mount Rectifier

FEATURES

- AEC-Q101 qualified
- Ideal for automated placement
- Compact package size, profile <0.85mm
- High surge current capability
- Low power loss, high efficiency
- Moisture sensitivity level: level 1, per J-STD-020
- RoHS Compliant
- Halogen-free according to IEC 61249-2-21

APPLICATIONS

- Low voltage, high freq. inverter
- DC/DC converter
- Freewheeling diodes
- Reverse battery protection
- Car lighting

MECHANICAL DATA

- Case: SOD-123HE
- Molding compound meets UL 94V-0 flammability rating
- Terminal: Matte tin plated leads, solderable per J-STD-002
- Meet JESD 201 class 2 whisker test
- Polarity: Indicated by cathode band
- Weight: 0.021g (approximately)

| KEY PARAMETERS | | |
|----------------|------------|------|
| PARAMETER | VALUE | UNIT |
| I_F | 1 | A |
| V_{RRM} | 20 - 150 | V |
| I_{FSM} | 30 | A |
| $T_{J\ MAX}$ | 125, 150 | °C |
| Package | SOD-123HE | |
| Configuration | Single die | |



SOD-123HE



| ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted) | | | | | | | | |
|--|--------------|--------------|----------|--------------|----------|-----------|-----------|------|
| PARAMETER | SYMBOL | SS12 LSH | SS13 LSH | SS14 LSH | SS16 LSH | SS110 LSH | SS115 LSH | UNIT |
| Marking code on the device | | 12LS | 13LS | 14LS | 16LS | 10LS | A5LS | |
| Repetitive peak reverse voltage | V_{RRM} | 20 | 30 | 40 | 60 | 100 | 150 | V |
| Reverse voltage, total rms value | $V_{R(RMS)}$ | 14 | 21 | 28 | 42 | 70 | 105 | V |
| Forward current | I_F | 1 | | | | | | A |
| Peak forward surge current, 8.3ms single half sine-wave superimposed on rated load | I_{FSM} | 30 | | | | | | A |
| Junction temperature | T_J | - 55 to +125 | | - 55 to +150 | | | | °C |
| Storage temperature | T_{STG} | - 55 to +150 | | | | | | °C |

| THERMAL PERFORMANCE | | | |
|--|-----------------|------------|-------------|
| PARAMETER | SYMBOL | TYP | UNIT |
| Junction-to-case thermal resistance | $R_{\theta JC}$ | 25 | °C/W |
| Junction-to-ambient thermal resistance | $R_{\theta JA}$ | 70 | °C/W |

| ELECTRICAL SPECIFICATIONS ($T_A = 25^\circ\text{C}$ unless otherwise noted) | | | | | | | | |
|---|--|---|---------------|---------------------------|------------|-------------|---|----|
| PARAMETER | | CONDITIONS | SYMBOL | TYP | MAX | UNIT | | |
| Forward voltage ⁽¹⁾ | SS12LSH | $I_F = 0.5\text{A}, T_J = 25^\circ\text{C}$ | V_F | - | - | V | | |
| | | $I_F = 1.0\text{A}, T_J = 25^\circ\text{C}$ | | - | 0.45 | V | | |
| | SS13LSH | $I_F = 0.5\text{A}, T_J = 25^\circ\text{C}$ | | - | - | V | | |
| | | $I_F = 1.0\text{A}, T_J = 25^\circ\text{C}$ | | - | 0.50 | V | | |
| | SS14LSH | $I_F = 0.5\text{A}, T_J = 25^\circ\text{C}$ | | - | 0.51 | V | | |
| | | $I_F = 1.0\text{A}, T_J = 25^\circ\text{C}$ | | - | 0.55 | V | | |
| | SS16LSH | $I_F = 0.5\text{A}, T_J = 25^\circ\text{C}$ | | - | 0.58 | V | | |
| | | $I_F = 1.0\text{A}, T_J = 25^\circ\text{C}$ | | - | 0.70 | V | | |
| | SS110LSH | $I_F = 0.5\text{A}, T_J = 25^\circ\text{C}$ | | - | 0.70 | V | | |
| | | $I_F = 1.0\text{A}, T_J = 25^\circ\text{C}$ | | - | 0.80 | V | | |
| | SS115LSH | $I_F = 0.5\text{A}, T_J = 25^\circ\text{C}$ | | - | 0.75 | V | | |
| | | $I_F = 1.0\text{A}, T_J = 25^\circ\text{C}$ | | - | 0.90 | V | | |
| Reverse current @ rated V_R ⁽²⁾ | SS12LSH SS13LSH SS14LSH SS16LSH | $T_J = 25^\circ\text{C}$ | I_R | - | 0.4 | mA | | |
| | | $T_J = 125^\circ\text{C}$ | | - | - | mA | | |
| | SS110LSH SS115LSH | $T_J = 25^\circ\text{C}$ | | - | 0.05 | mA | | |
| | | $T_J = 125^\circ\text{C}$ | | - | 0.5 | mA | | |
| | Junction capacitance | | | 1MHz, $V_R = 4.0\text{V}$ | C_J | 80 | - | pF |

Notes:

1. Pulse test with $PW = 0.3\text{ms}$
2. Pulse test with $PW = 30\text{ms}$

| ORDERING INFORMATION | | |
|------------------------------------|----------------|----------------------|
| ORDERING CODE⁽¹⁾ | PACKAGE | PACKING |
| SS1xLSH | SOD-123HE | 10,000 / Tape & Reel |

Notes:

1. "x" defines voltage from 20V(SS12LSH) to 150V(SS115LSH)

CHARACTERISTICS CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)

Fig.1 Forward Current Derating Curve




Fig.2 Typical Junction Capacitance




Fig.3 Typical Reverse Characteristics




Fig.4 Typical Forward Characteristics






Fig.5 Maximum Non-Repetitive Forward Surge Current




PACKAGE OUTLINE DIMENSIONS

SOD-123HE



| DIM. | Unit (mm) | | Unit (inch) | |
|------|-----------|------|-------------|-------|
| | Min. | Max. | Min. | Max. |
| A | 0.75 | 0.85 | 0.030 | 0.033 |
| A1 | 0.00 | 0.02 | 0.000 | 0.001 |
| b | 0.85 | 1.15 | 0.033 | 0.045 |
| b2 | 0.95 | 1.25 | 0.037 | 0.049 |
| c | 0.10 | 0.20 | 0.004 | 0.008 |
| D | 1.65 | 1.95 | 0.065 | 0.077 |
| E | 3.50 | 3.90 | 0.138 | 0.154 |
| E1 | 2.60 | 3.00 | 0.102 | 0.118 |
| E2 | 1.90 | 2.30 | 0.075 | 0.091 |
| E3 | 1.35 | 1.55 | 0.053 | 0.061 |
| L | 0.55 | 0.75 | 0.022 | 0.030 |
| L1 | 0.35 | 0.55 | 0.014 | 0.022 |

SUGGESTED PAD LAYOUT



| Symbol | Unit (mm) | Unit (inch) |
|--------|-----------|-------------|
| A | 1.40 | 0.055 |
| B | 2.40 | 0.094 |
| C | 0.70 | 0.028 |
| D | 0.90 | 0.035 |
| E | 1.40 | 0.055 |

MARKING DIAGRAM



P/N = Marking Code
 YW = Date Code
 F = Factory Code

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Purchasers are solely responsible for the choice, selection, and use of TSC products and TSC assumes no liability for application assistance or the design of Purchasers' products.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.