

Touch panel - TP 5170T - 2700623

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Touch panel with 43,0 cm (17 in.) graphics-capable TFT display, 65,535 colors, 1280 x 1024 pixels, 2x Ethernet, 4x USB, 1x RS-232, 1x VGA and integrated runtime of the Visu+ visualization software

Product Features

- Visu+ RT and AX OPC server integrated as standard in all devices

Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	1.0 GRM
Custom tariff number	84714100
Country of origin	Taiwan

Technical data

Dimensions

External dimension, width	452 mm
External dimension, height	356.5 mm
External dimension, depth	10 mm
Installation dimension, width	424 mm
Installation dimension, height	329.5 mm

Display

Display	43,2 cm / 17"-TFT
Resolution	1280 x 1024 Pixel (SXGA)
Backlighting	CCFL
Display backlight MTBF	50000 h
Touch screen	Resistive industrial touch screen
Colors	65,536 colors

Computer data

Processor	Intel® Atom™ N270 1,6 GHz
RAM	1 GB DDR

Touch panel - TP 5170T - 2700623

Technical data

Computer data

Mass storage	CompactFlash®, 2 GB
Interfaces	COM 1 (RS-232), 1x VGA, 4x USB, 2x CompactFlash®
Network	2x Ethernet (10/100/1000 Mbps), RJ45
Operating systems	Windows CE 6.0
Realtime clock	Yes (battery-backed)
Service life of battery	5 years (typical)
Power supply unit	24 V DC ±20 %

General

Mounting type	Installation in front plate
---------------	-----------------------------

Ambient conditions

Degree of protection	IP65 (front), IP20 (back)
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Permissible humidity (operation)	5 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	5 % ... 95 % (non-condensing)
Vibration (operation)	DIN EN 60068-2-6
Shock	15g, 11 ms in accordance with IEC 60068-2-27

Classifications

eCl@ss

eCl@ss 4.0	27330202
eCl@ss 4.1	27330202
eCl@ss 5.0	27242215
eCl@ss 5.1	27242301
eCl@ss 6.0	27242301
eCl@ss 7.0	27242301
eCl@ss 8.0	27242301

ETIM

ETIM 3.0	EC001426
ETIM 4.0	EC001414
ETIM 5.0	EC001414

UNSPSC

UNSPSC 6.01	43172015
-------------	----------

Touch panel - TP 5170T - 2700623

Classifications

UNSPSC

UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404

Approvals

Approvals


Approvals


UL Listed / cUL Listed / cULus Listed

Ex Approvals

Approvals submitted

Approval details

UL Listed 

cUL Listed 

cULus Listed 