

Aug.1.2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					△				
△					△				
APPLICABLE STANDARD									
RATING	OPERATING TEMPERATURE RANGE	-40℃ ~ +85℃			STORAGE TEMPERATURE RANGE	-10℃ ~ +50℃ (Packed Condition)			
	VOLTAGE	50V [AC(rms) / DC]			OPERATING OR STORAGE HUMIDITY RANGE	RELATIVE HUMIDITY 90%MAX (NOT DEWED)			
	CURRENT	0.5A [AC(rms) / DC] (note1)			APPLICABLE CABLE	FFC(t=0.3±0.03mm)			
SPECIFICATIONS									
ITEM		TEST METHOD			REQUIREMENTS			QT	AT
CONSTRUCTION									
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT			ACCORDING TO DRAWING			0	0
MARKING		CONFIRMED VISUALLY						0	0
ELECTRICAL CHARACTERISTICS									
CONTACT RESISTANCE		MATE APPLICABLE FPC/FFC AND APPLY A CURRENT OF 10mA, 20mv DC			50 mΩ MAX. INCLUDING FPC/FFC BULK RESISTANCE(L=8mm)			0	0
INSULATION RESISTANCE		MATE APPLICABLE FPC/FFC AND APPLY A VOLTAGE OF DC 500V			500 MΩ MIN.			0	0
VOLTAGE PROOF		MATE APPLICABLE FPC/FFC AND APPLY A VOLTAGE OF AC 250V FOR 1 min.			NO FLASHOVER OR BREAKDOWN.			0	0
MECHANICAL CHARACTERISTICS									
FFC RETENSION FORCE		MEASURE BY APPLICABLE FPC/FFC(t=0.3) AT INITIAL CONDITION			①VERTICAL DIRECTION : 9.8N MIN. ②HORIZONTAL DIRECTION : 19.6N MIN.			0	-
MECHANICAL OPERATION		20 TIMES INSERTIONS AND EXTRATIONS			①CONTACT RESISTANCE: 50mΩ MAX ②NO DAMAGE, CRACK AND LOOSENESS OF PARTS			0	-
VIBRATION		FREQUENCY 10 ~ 55 Hz, TOTAL AMPLITUDE 1.5 mm AT 2h, IN 3 DIRECTIONS			①NO ELECTRICAL DISCONTINUITY OF 1μs. ②CONTACT RESISTANCE : 50mΩ MAX			0	-
SHOCK		490m/s ² DIRECTION OF PULSE 11ms AT 3 TIMES IN 3 DIRECTIONS.			③NO DAMAGE, CRACK AND LOOSENESS OF PARTS			0	-
ENVIRONMENTAL CHARACTERISTICS									
DAMP HEAT(STEADY STATE)		EXPOSED AT 40±2℃, 90~95 %, 96Hr.			①CONTACT RESISTANCE: 50 mΩ MAX. ②INSULATION RESISTANCE: 100 MΩ MIN. ③NO DAMAGE, CRACK OR LOOSENESS OF PARTS.			0	-
RAPID CHAGE OF TEMPERATURE		TEMPERATURE : -40±2 → 15~35 → +85±2 → 15~35 ℃ TIME : 30 → 2~3 → 30 → 2~3 min. UNDER 5 CYCLES.						0	-
DAMP HEAT, CYCLE		TEMPERATURE -10→+65 HUMIDITY : 90~95% 10 CYCLE(240Hr)						0	-
DRY HEAT		EXPOSED AT 85±2℃, 96Hr			①CONTACT RESISTANCE : 50mΩ MAX ②NO DAMAGE, CRACK OR LOOSENESS OF PARTS.			0	-
COLD		EXPOSED AT -40±2℃, 96Hr						0	-
CORROSION SALT SPRAY		EXPOSED AT 35±2℃, 5±1% SALT WATER SPRAY FOR 48Hr			①CONTACT RESISTANCE 50mΩ MAX ②NO DAMAGE, CRACK OR LOOSENESS OF PARTS. ③NO EVIDENCE OF CORROSION WHICH AFFECTS TO OPERATION OF CONNECTOR.			0	-
HYDROGEN SULPHIDE		EXPOSED IN 3 PPM FOR 96Hr. (TEST STANDARD : JEIDA-38)						0	-
RESISTANCE TO SOLDERING HEAT		REFLOW SOLDERING: PEAK TMP. : 260℃ MAX. 10s MIN. REFLOW TMP. : 217℃ FOR 90~120s			①NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS. ②NO DAMAGE OF ELECTRICAL PERFORMANCE			0	-
SOLDER ABILITY		SOLDERED AT SOLDER TEMPERATURE, 245±3℃ FOR IMMERSION DURATION, 3±0.3 SEC			A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95% OF THE SURFACE BEING EMMERSED.			0	-
(note 1) WHEN THE SAME VALUE OF CURRENT ARE APPLIED TO ALL CONTACTS AT THE SAME TIME IN ONCE, SET THE CURRENT TO THE 70% OF THE RATED CURRENT VALUE.									
REMARKS CONDITIONS FOR TESTING				DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED	
				M.G.KANG	M.G.KANG	D.H.CHO	H.C.SONG	ENG 17.02.23 DEPT	
UNLESS OTHERWISE SPECIFIED, REFER TO JIS C 5402.				14.09.16	14.09.16	14.09.16	14.09.16		
NOTE QT: QUALIFICATION TEST AT: ASSURANCE TEST O: APPLICABLE TEST									
HIROSE KOREA CO.,LTD.			SPECIFICATION SHEET			PART NO. TF49-50S-0.5SH(800)			
CODE NO.(OLD)		DRAWING NO.		CODE NO.				1/1	
CL		ELC4-631681-80		CL 6545-0001-5-800				1/1	