

Power Tool Accessories and Systems

The next generation of Klein tools is now available for use with power tools. Klein offers a line of Multi-Bit Drivers, Hollow-Shaft Nut Drivers, Power Driver Bits and Conduit Reamers available as accessories for power tools. Featuring the same functionality, quality and performance you expect from Klein.

For Professionals... Since 1857™



Drill Tap Set

- For aluminum, brass, copper, plastic, and mild steel
- 1/4" hex for easier application with quick connect
- Set of six tap sizes plus two extra of the smallest taps
- For use on up to 10 gauge metal
- Made of high speed steel for added durability

Cat. No.	Tap Sizes Included	Weight
32217	6-32 (2), 8-32 (2), 10-24, 10-32, 12-24, 1/4-20	1.5 lbs. (0.68 kg)
Replacement Taps		
32237	6-32 Drill Tap	4.0 oz. (113 g)
32238	8-32 Drill Tap	4.0 oz. (113 g)
32239	10-32 Drill Tap	4.0 oz. (113 g)
32240	10-24 Drill Tap	4.0 oz. (113 g)
32241	12-24 Drill Tap	4.0 oz. (113 g)
32242	1/4-20 Drill Tap	4.0 oz. (113 g)




32217

NOTE: Read and follow safety instructions in power tool owner's manual.

Power Drivers

- Klein Power Drivers are manufactured in the U.S.A. to ensure proper fit in every application.
 Each Power Driver is precision machined, heat treated and finished to the gold standards
 Klein Tools puts into every screwdriver blade. Proprietary processes create the longest life power driver bit in the industry. Tight fitting tips reduce wear and deliver the premium performance you expect from a Klein.
- Precision machined for better fit, more torque and less wear
- Custom heat treated for long life
- Available in a variety of tips





Cat. No.	Tip Size	Length	Package Quantity	Weight
PH115	#1 Phillips	1" (25.4 mm)	5	1.6 oz. (45 g)
PH1355	#1 Phillips	3-1/2" (88.9 mm)	5	3.8 oz. (108 g)
PH162	#1 Phillips	6" (152.4 mm)	2	2.9 oz. (82 g)
PH2115	#2 Phillips	1" (25.4 mm)	15	3.2 oz. (91 g)
PH2355	#2 Phillips	3-1/2" (88.9 mm)	5	4.2 oz. (119 g)
PH262	#2 Phillips	6" (152.4 mm)	2	3.0 oz. (85 g)
PH315	#3 Phillips	1" (25.4 mm)	5	1.6 oz. (45 g)
PH3355	#3 Phillips	3-1/2" (88.9 mm)	5	4.2 oz. (119 g)
PH362	#3 Phillips	6" (152.4 mm)	2	2.9 oz. (82 g)
SL31615	3/16" (4.8 mm) Slotted	1" (25.4 mm)	5	1.6 oz. (45 g)
SL316355	3/16" (4.8 mm) Slotted	3-1/2" (88.9 mm)	5	3.8 oz. (108 g)
SL1415	1/4" (6.4 mm) Slotted	1" (25.4 mm)	5	1.6 oz. (45 g)
SL14355	1/4" (6.4 mm) Slotted	3-1/2" (88.9 mm)	5	3.8 oz. (108 g)





Power Driver Sets

- Precision machined for better fit, more torque and less wear
- Custom heat treated for long life



Cat. No.	Description	Phillips Bits	Slotted Bits	Square Bits	Overall Length	Weight
32234	3-1/2" Power Driver Set, Assorted Bits	#1 and #2	1/4" (6.4 mm)	#1 and #2	3-1/2" (88.9 mm)	3.8 oz. (108 g)
32235	6" Power Driver Set, #1 and #3 Phillips	#1 and #3	_	_	6" (152.4 mm)	3.2 oz. (91 g)



32234

Power Conduit Reamer

Designed to fit into power drill chucks and quick release adapters, the power conduit reamer reduces time and wrist fatigue on projects with large quantities of conduit runs



- Designed to fit into power drill chu ks and 1/4" guick release
- Reams 1/2", 3/4" and 1" conduit in a fraction of the time
- Includes replaceable No. 2 square recess bit for installing conduit fittings
- Includes precision engineered replaceable reaming blade





Cat. No.	Description	Item	Weight
85091	Power Conduit Reamer	Conduit Reamer Drill Head for 1/2", 3/4", 1"	5.3 oz. (150 g)
Replacemen	it Parts		
19353	Conduit Reamer Replacement Blade Kit	Conduit Reamer Replacement Blade	0.16 oz. (4.5 g)

Power Nut Drivers

- Available in several sizes, these hollow shaft magnetic nut drivers are designed for long bolts, studs or threaded rod jobs. The magnetic head holds nuts and bolts to aid in hard to reach installations. The 5" and 10" models feature a wrench assist end, designed for high torque loosening found in many jobs.
- 5" (127 mm) and 10" (254 mm) models are sold individually
- Power Nut Driver Set contains 1/4", 5/16" and 3/8" nut drivers (Cat. No. 32759)



Hollow magnetic* shafts for nut running



PND71610

	×9	
PNE	7165	32759
		-Name -

Cat. No.	Hex Size	Hollow Depth	Overall Length
2" (127 mm) Ou	t-of-Chuck		
32759	1/4", 5/16", 3/8"	1-7/8" (47.6 mm)	6-5/16" (160.3 mm)
5" (127 mm) Ou	t-of-Chuck		
PND7165	7/16"	3-11/16" (93.7 mm)	6-5/16" (160.3 mm)
PND125	1/2"	3-23/32" (94.5 mm)	6-19/64" (159.9 mm)
PND9165	9/16"	3-5/8" (92.1 mm)	6+21/64 (160.7 mm)
10" (254 mm) 0	ut-of-Chuck		
PND71610	7/16"	8-13/16" (223.8 mm)	11-5/16" (287.3 mm)
PND1210	1/2"	8-23/32" (221.5 mm)	11-19/64" (286.9 mm)
PND91610	9/16"	8-5/8" (219.1 mm)	11-5/16" (287.3 mm)
	net is globally sourced.	0 0/0 (210.1 11111)	11 0/10 (207.0 11111)

NOTE: Read and follow safety instructions in power tool owner's manual.

See page 310 for additional information on warnings.





