



PANEL CUTOUT

SPECIFICATIONS:

Housing: Thermoplastic, UL-94V-0 rated
 Contacts: Copper alloy
 Electrical ratings: 660W, 600V
 Max. Operating temperature: 120°C
 Applicable Wire type: 18AWG solid copper
 Conductor strip length: 9.5mm
 Applicable Panel thickness: 1.0 - 1.5mm
 For T8 bulb type
 For G13 Base
 For Rapid Start (I)

Certifications:

UL 542
 UL 496
 CSA 22.2 / 43



RoHS
 COMPLIANT

REVISIONS

REV	DATE	CHANGE	CHK	CHK	APPR
A	11/16/17	UPDATED DRAWING	PB		

TOLERANCE
 UNLESS OTHERWISE SPECIFIED
 X ± 1
 X.X ± 0.4
 X.XX ± 0.13

Power Dynamics, Inc.

Phone: 973 560-0019 Whippany, New Jersey Fax: 973 560-0076

PART: FLUORESCENT / LED T8 LAMPHOLDER FOR G13 BASE
 MEDIUM BI-PIN; NON-SHUNTED; TURN TYPE WITH LOCK
 FOR RAPID START; MEDIUM HEIGHT

DRAWN BY	PB	DATE:	10/26/17
CHECK BY		DATE:	
APPR BY		DATE:	

PART #:	PD-FL-18-11	SHEET	1 of 1
SIZE:	A	ALL DIMENSIONS FOR REFERENCE ONLY	A
SCALE:	NTS	DIMENSIONS ARE IN MILLIMETERS	REV: