



SIRIUS soft starter 200-600 V 470 A, 110-250 V AC spring-type terminals  
Analog output

|                                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|---------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>product brand name</b>                               | SIRIUS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>product category</b>                                 | Hybrid switching devices                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>product designation</b>                              | Soft starter                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>product type designation</b>                         | 3RW52                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>manufacturer's article number</b>                    | <ul style="list-style-type: none"> <li>• of standard HMI module usable <a href="#">3RW5980-0HS00</a></li> <li>• of high feature HMI module usable <a href="#">3RW5980-0HF00</a></li> <li>• of communication module PROFINET standard usable <a href="#">3RW5980-0CS00</a></li> <li>• of communication module PROFIBUS usable <a href="#">3RW5980-0CP00</a></li> <li>• of communication module Modbus TCP usable <a href="#">3RW5980-0CT00</a></li> <li>• of communication module Modbus RTU usable <a href="#">3RW5980-0CR00</a></li> <li>• of communication module Ethernet/IP <a href="#">3RW5980-0CE00</a></li> <li>• of circuit breaker usable at 400 V <a href="#">3VA2450-7MN32-0AA0: Type of coordination 1, Iq = 65 kA, CLASS 10</a></li> <li>• of circuit breaker usable at 500 V <a href="#">3VA2450-7MN32-0AA0: Type of coordination 1, Iq = 65 kA, CLASS 10</a></li> <li>• of circuit breaker usable at 400 V at inside-delta circuit <a href="#">3VA2510-6HN32-0AA0: Type of coordination 1, Iq = 65 kA, CLASS 10</a></li> <li>• of circuit breaker usable at 500 V at inside-delta circuit <a href="#">3VA2510-6HN32-0AA0: Type of coordination 1, Iq = 65 kA, CLASS 10</a></li> <li>• of the gG fuse usable up to 690 V 2x3NA3365-6; Type of coordination 1, Iq = 65 kA</li> <li>• of the gG fuse usable at inside-delta circuit up to 500 V 2x3NA3365-6; Type of coordination 1, Iq = 65 kA</li> <li>• of full range R fuse link for semiconductor protection usable up to 690 V <a href="#">3NE1436-2: Type of coordination 2, Iq = 65 kA</a></li> <li>• of back-up R fuse link for semiconductor protection usable up to 690 V <a href="#">3NE3340-8: Type of coordination 2, Iq = 65 kA</a></li> </ul> |
| <b>General technical data</b>                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>starting voltage [%]</b>                             | 30 ... 100 %                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>stopping voltage [%]</b>                             | 50 %; non-adjustable                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>start-up ramp time of soft starter</b>               | 0 ... 20 s                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>current limiting value [%] adjustable</b>            | 130 ... 700 %                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>certificate of suitability</b>                       | <ul style="list-style-type: none"> <li>• CE marking Yes</li> <li>• UL approval Yes</li> <li>• CSA approval Yes</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>product component</b>                                | <ul style="list-style-type: none"> <li>• HMI-High Feature No</li> <li>• is supported HMI-Standard Yes</li> <li>• is supported HMI-High Feature Yes</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>product feature integrated bypass contact system</b> | Yes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>number of controlled phases</b>                      | 3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |

|                                                                                     |                                                                                 |
|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------|
| <b>trip class</b>                                                                   | CLASS 10A (default) / 10E / 20E; acc. to IEC 60947-4-2                          |
| <b>buffering time in the event of power failure</b>                                 |                                                                                 |
| • for main current circuit                                                          | 100 ms                                                                          |
| • for control circuit                                                               | 100 ms                                                                          |
| insulation voltage rated value                                                      | 600 V                                                                           |
| <b>degree of pollution</b>                                                          | 3, acc. to IEC 60947-4-2                                                        |
| <b>impulse voltage rated value</b>                                                  | 6 kV                                                                            |
| <b>blocking voltage of the thyristor maximum</b>                                    | 1 600 V                                                                         |
| <b>service factor</b>                                                               | 1                                                                               |
| <b>surge voltage resistance rated value</b>                                         | 6 kV                                                                            |
| <b>maximum permissible voltage for safe isolation</b>                               |                                                                                 |
| • between main and auxiliary circuit                                                | 600 V                                                                           |
| <b>shock resistance</b>                                                             | 15 g / 11 ms, from 12 g / 11 ms with potential contact lifting                  |
| <b>vibration resistance</b>                                                         | 15 mm to 6 Hz; 2g to 500 Hz                                                     |
| utilization category according to IEC 60947-4-2                                     | AC 53a                                                                          |
| <b>reference code according to IEC 81346-2</b>                                      | Q                                                                               |
| <b>Substance Prohibitance (Date)</b>                                                | 02/15/2018                                                                      |
| <b>product function</b>                                                             |                                                                                 |
| • ramp-up (soft starting)                                                           | Yes                                                                             |
| • ramp-down (soft stop)                                                             | Yes                                                                             |
| • Soft Torque                                                                       | Yes                                                                             |
| • adjustable current limitation                                                     | Yes                                                                             |
| • pump ramp down                                                                    | Yes                                                                             |
| • intrinsic device protection                                                       | Yes                                                                             |
| • motor overload protection                                                         | Yes; Electronic motor overload protection                                       |
| • evaluation of thermistor motor protection                                         | No                                                                              |
| • inside-delta circuit                                                              | Yes                                                                             |
| • auto-RESET                                                                        | Yes                                                                             |
| • manual RESET                                                                      | Yes                                                                             |
| • remote reset                                                                      | Yes; By turning off the control supply voltage                                  |
| • communication function                                                            | Yes                                                                             |
| • operating measured value display                                                  | Yes; Only in conjunction with special accessories                               |
| • error logbook                                                                     | Yes; Only in conjunction with special accessories                               |
| • via software parameterizable                                                      | No                                                                              |
| • via software configurable                                                         | Yes                                                                             |
| • <b>PROFenergy</b>                                                                 | Yes; in connection with the PROFINET Standard communication module              |
| • <b>firmware update</b>                                                            | Yes                                                                             |
| • <b>removable terminal for control circuit</b>                                     | Yes                                                                             |
| • torque control                                                                    | No                                                                              |
| • analog output                                                                     | Yes; 4 ... 20 mA (default) / 0 ... 10 V (parameterizable with High Feature HMI) |
| <b>Power Electronics</b>                                                            |                                                                                 |
| <b>operational current</b>                                                          |                                                                                 |
| • at 40 °C rated value                                                              | 470 A                                                                           |
| • at 50 °C rated value                                                              | 416 A                                                                           |
| • at 60 °C rated value                                                              | 380 A                                                                           |
| <b>operational current at inside-delta circuit</b>                                  |                                                                                 |
| • at 40 °C rated value                                                              | 814 A                                                                           |
| • at 50 °C rated value                                                              | 721 A                                                                           |
| • at 60 °C rated value                                                              | 658 A                                                                           |
| <b>operating voltage</b>                                                            |                                                                                 |
| • rated value                                                                       | 200 ... 600 V                                                                   |
| • at inside-delta circuit rated value                                               | 200 ... 600 V                                                                   |
| <b>relative negative tolerance of the operating voltage</b>                         | -15 %                                                                           |
| <b>relative positive tolerance of the operating voltage</b>                         | 10 %                                                                            |
| <b>relative negative tolerance of the operating voltage at inside-delta circuit</b> | -15 %                                                                           |
| <b>relative positive tolerance of the operating voltage at inside-delta circuit</b> | 10 %                                                                            |
| <b>operating power for 3-phase motors</b>                                           |                                                                                 |

|                                                                          |                                        |
|--------------------------------------------------------------------------|----------------------------------------|
| • at 230 V at 40 °C rated value                                          | 132 kW                                 |
| • at 230 V at inside-delta circuit at 40 °C rated value                  | 250 kW                                 |
| • at 400 V at 40 °C rated value                                          | 250 kW                                 |
| • at 400 V at inside-delta circuit at 40 °C rated value                  | 400 kW                                 |
| • at 500 V at 40 °C rated value                                          | 315 kW                                 |
| • at 500 V at inside-delta circuit at 40 °C rated value                  | 500 kW                                 |
| <b>Operating frequency 1 rated value</b>                                 | 50 Hz                                  |
| <b>Operating frequency 2 rated value</b>                                 | 60 Hz                                  |
| <b>relative negative tolerance of the operating frequency</b>            | -10 %                                  |
| <b>relative positive tolerance of the operating frequency</b>            | 10 %                                   |
| <b>adjustable motor current</b>                                          |                                        |
| • at rotary coding switch on switch position 1                           | 200 A                                  |
| • at rotary coding switch on switch position 2                           | 218 A                                  |
| • at rotary coding switch on switch position 3                           | 236 A                                  |
| • at rotary coding switch on switch position 4                           | 254 A                                  |
| • at rotary coding switch on switch position 5                           | 272 A                                  |
| • at rotary coding switch on switch position 6                           | 290 A                                  |
| • at rotary coding switch on switch position 7                           | 308 A                                  |
| • at rotary coding switch on switch position 8                           | 326 A                                  |
| • at rotary coding switch on switch position 9                           | 344 A                                  |
| • at rotary coding switch on switch position 10                          | 362 A                                  |
| • at rotary coding switch on switch position 11                          | 380 A                                  |
| • at rotary coding switch on switch position 12                          | 398 A                                  |
| • at rotary coding switch on switch position 13                          | 416 A                                  |
| • at rotary coding switch on switch position 14                          | 434 A                                  |
| • at rotary coding switch on switch position 15                          | 452 A                                  |
| • at rotary coding switch on switch position 16                          | 470 A                                  |
| • minimum                                                                | 200 A                                  |
| <b>adjustable motor current</b>                                          |                                        |
| • for inside-delta circuit at rotary coding switch on switch position 1  | 346 A                                  |
| • for inside-delta circuit at rotary coding switch on switch position 2  | 378 A                                  |
| • for inside-delta circuit at rotary coding switch on switch position 3  | 409 A                                  |
| • for inside-delta circuit at rotary coding switch on switch position 4  | 440 A                                  |
| • for inside-delta circuit at rotary coding switch on switch position 5  | 471 A                                  |
| • for inside-delta circuit at rotary coding switch on switch position 6  | 502 A                                  |
| • for inside-delta circuit at rotary coding switch on switch position 7  | 533 A                                  |
| • for inside-delta circuit at rotary coding switch on switch position 8  | 565 A                                  |
| • for inside-delta circuit at rotary coding switch on switch position 9  | 596 A                                  |
| • for inside-delta circuit at rotary coding switch on switch position 10 | 627 A                                  |
| • for inside-delta circuit at rotary coding switch on switch position 11 | 658 A                                  |
| • for inside-delta circuit at rotary coding switch on switch position 12 | 689 A                                  |
| • for inside-delta circuit at rotary coding switch on switch position 13 | 721 A                                  |
| • for inside-delta circuit at rotary coding switch on switch position 14 | 752 A                                  |
| • for inside-delta circuit at rotary coding switch on switch position 15 | 783 A                                  |
| • for inside-delta circuit at rotary coding switch on switch position 16 | 814 A                                  |
| • at inside-delta circuit minimum                                        | 346 A                                  |
| <b>minimum load [%]</b>                                                  | 15 %; Relative to smallest settable le |
| <b>power loss [W] for rated value of the current at AC</b>               |                                        |

|                                                                                                                                                   |                                                                                                                                                                                                                                    |
|---------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>• at 40 °C after startup</li> <li>• at 50 °C after startup</li> <li>• at 60 °C after startup</li> </ul>    | 153 W<br>137 W<br>126 W                                                                                                                                                                                                            |
| <b>power loss [W] at AC at current limitation 350 %</b>                                                                                           |                                                                                                                                                                                                                                    |
| <ul style="list-style-type: none"> <li>• at 40 °C during startup</li> <li>• at 50 °C during startup</li> <li>• at 60 °C during startup</li> </ul> | 7 903 W<br>6 604 W<br>5 794 W                                                                                                                                                                                                      |
| <b>Control circuit/ Control</b>                                                                                                                   |                                                                                                                                                                                                                                    |
| <b>type of voltage of the control supply voltage</b>                                                                                              | AC                                                                                                                                                                                                                                 |
| <b>control supply voltage at AC</b>                                                                                                               |                                                                                                                                                                                                                                    |
| <ul style="list-style-type: none"> <li>• at 50 Hz</li> <li>• at 60 Hz</li> </ul>                                                                  | 110 ... 250 V<br>110 ... 250 V                                                                                                                                                                                                     |
| <b>relative negative tolerance of the control supply voltage at AC at 50 Hz</b>                                                                   | -15 %                                                                                                                                                                                                                              |
| <b>relative positive tolerance of the control supply voltage at AC at 50 Hz</b>                                                                   | 10 %                                                                                                                                                                                                                               |
| <b>relative negative tolerance of the control supply voltage at AC at 60 Hz</b>                                                                   | -15 %                                                                                                                                                                                                                              |
| <b>relative positive tolerance of the control supply voltage at AC at 60 Hz</b>                                                                   | 10 %                                                                                                                                                                                                                               |
| <b>control supply voltage frequency</b>                                                                                                           | 50 ... 60 Hz                                                                                                                                                                                                                       |
| <b>relative negative tolerance of the control supply voltage frequency</b>                                                                        | -10 %                                                                                                                                                                                                                              |
| <b>relative positive tolerance of the control supply voltage frequency</b>                                                                        | 10 %                                                                                                                                                                                                                               |
| <b>control supply current in standby mode rated value</b>                                                                                         | 30 mA                                                                                                                                                                                                                              |
| <b>holding current in bypass operation rated value</b>                                                                                            | 100 mA                                                                                                                                                                                                                             |
| <b>locked-rotor current at close of bypass contact maximum</b>                                                                                    | 2.2 A                                                                                                                                                                                                                              |
| <b>inrush current peak at application of control supply voltage maximum</b>                                                                       | 12.2 A                                                                                                                                                                                                                             |
| <b>duration of inrush current peak at application of control supply voltage</b>                                                                   | 2.2 ms                                                                                                                                                                                                                             |
| <b>design of the overvoltage protection</b>                                                                                                       | Varistor                                                                                                                                                                                                                           |
| <b>design of short-circuit protection for control circuit</b>                                                                                     | 4 A gG fuse (I <sub>cu</sub> =1 kA), 6 A quick-acting fuse (I <sub>cu</sub> =1 kA), C1 miniature circuit breaker (I <sub>cu</sub> = 600 A), C6 miniature circuit breaker (I <sub>cu</sub> = 300 A); Is not part of scope of supply |
| <b>Inputs/ Outputs</b>                                                                                                                            |                                                                                                                                                                                                                                    |
| <b>number of digital inputs</b>                                                                                                                   | 1                                                                                                                                                                                                                                  |
| <b>number of digital outputs</b>                                                                                                                  | 3                                                                                                                                                                                                                                  |
| <ul style="list-style-type: none"> <li>• not parameterizable</li> </ul>                                                                           | 2                                                                                                                                                                                                                                  |
| <b>digital output version</b>                                                                                                                     | 2 normally-open contacts (NO) / 1 changeover contact (CO)                                                                                                                                                                          |
| <b>number of analog outputs</b>                                                                                                                   | 1                                                                                                                                                                                                                                  |
| <b>switching capacity current of the relay outputs</b>                                                                                            |                                                                                                                                                                                                                                    |
| <ul style="list-style-type: none"> <li>• at AC-15 at 250 V rated value</li> <li>• at DC-13 at 24 V rated value</li> </ul>                         | 3 A<br>1 A                                                                                                                                                                                                                         |
| <b>Installation/ mounting/ dimensions</b>                                                                                                         |                                                                                                                                                                                                                                    |
| <b>mounting position</b>                                                                                                                          | with vertical mounting surface +/-90° rotatable, with vertical mounting surface +/- 22.5° tiltable to the front and back                                                                                                           |
| <b>fastening method</b>                                                                                                                           | screw fixing                                                                                                                                                                                                                       |
| <b>height</b>                                                                                                                                     | 393 mm                                                                                                                                                                                                                             |
| <b>width</b>                                                                                                                                      | 210 mm                                                                                                                                                                                                                             |
| <b>depth</b>                                                                                                                                      | 203 mm                                                                                                                                                                                                                             |
| <b>required spacing with side-by-side mounting</b>                                                                                                |                                                                                                                                                                                                                                    |
| <ul style="list-style-type: none"> <li>• forwards</li> <li>• backwards</li> <li>• upwards</li> <li>• downwards</li> <li>• at the side</li> </ul>  | 10 mm<br>0 mm<br>100 mm<br>75 mm<br>5 mm                                                                                                                                                                                           |
| <b>weight without packaging</b>                                                                                                                   | 9.9 kg                                                                                                                                                                                                                             |
| <b>Connections/ Terminals</b>                                                                                                                     |                                                                                                                                                                                                                                    |
| <b>type of electrical connection</b>                                                                                                              |                                                                                                                                                                                                                                    |

|                                                                                                                                                                                                                                                                                                |                                                                                                                  |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>• for main current circuit</li> <li>• for control circuit</li> </ul>                                                                                                                                                                                    | busbar connection<br>spring-loaded terminals                                                                     |
| <b>width of connection bar maximum</b>                                                                                                                                                                                                                                                         | 45 mm                                                                                                            |
| <b>type of connectable conductor cross-sections</b>                                                                                                                                                                                                                                            |                                                                                                                  |
| <ul style="list-style-type: none"> <li>• for DIN cable lug for main contacts stranded</li> <li>• for DIN cable lug for main contacts finely stranded</li> </ul>                                                                                                                                | 2x (50 ... 240 mm <sup>2</sup> )<br>2x (70 ... 240 mm <sup>2</sup> )                                             |
| <b>type of connectable conductor cross-sections</b>                                                                                                                                                                                                                                            |                                                                                                                  |
| <ul style="list-style-type: none"> <li>• for control circuit solid</li> <li>• for control circuit finely stranded with core end processing</li> <li>• at AWG cables for control circuit solid</li> <li>• at AWG cables for control circuit finely stranded with core end processing</li> </ul> | 2x (0.25 ... 1.5 mm <sup>2</sup> )<br>2x (0.25 ... 1.5 mm <sup>2</sup> )<br><br>2x (24 ... 16)<br>2x (24 ... 16) |
| <b>wire length</b>                                                                                                                                                                                                                                                                             |                                                                                                                  |
| <ul style="list-style-type: none"> <li>• between soft starter and motor maximum</li> <li>• at the digital inputs at AC maximum</li> </ul>                                                                                                                                                      | 800 m<br>100 m                                                                                                   |
| <b>tightening torque</b>                                                                                                                                                                                                                                                                       |                                                                                                                  |
| <ul style="list-style-type: none"> <li>• for main contacts with screw-type terminals</li> <li>• for auxiliary and control contacts with screw-type terminals</li> </ul>                                                                                                                        | 14 ... 24 N·m<br>0.8 ... 1.2 N·m                                                                                 |
| <b>tightening torque [lbf·in]</b>                                                                                                                                                                                                                                                              |                                                                                                                  |
| <ul style="list-style-type: none"> <li>• for main contacts with screw-type terminals</li> <li>• for auxiliary and control contacts with screw-type terminals</li> </ul>                                                                                                                        | 124 ... 210 lbf·in<br>7 ... 10.3 lbf·in                                                                          |

### Ambient conditions

|                                                                                                                                                                                                 |                                                                                                                                                                                                                                                                                   |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| installation altitude at height above sea level maximum                                                                                                                                         | 5 000 m; Derating as of 1000 m, see catalog                                                                                                                                                                                                                                       |
| <b>ambient temperature</b>                                                                                                                                                                      |                                                                                                                                                                                                                                                                                   |
| <ul style="list-style-type: none"> <li>• during operation</li> <li>• during storage and transport</li> </ul>                                                                                    | -25 ... +60 °C; Please observe derating at temperatures of 40 °C or above<br>-40 ... +80 °C                                                                                                                                                                                       |
| <b>environmental category</b>                                                                                                                                                                   |                                                                                                                                                                                                                                                                                   |
| <ul style="list-style-type: none"> <li>• during operation according to IEC 60721</li> <li>• during storage according to IEC 60721</li> <li>• during transport according to IEC 60721</li> </ul> | 3K6 (no ice formation, only occasional condensation), 3C3 (no salt mist), 3S2 (sand must not get into the devices), 3M6<br>1K6 (only occasional condensation), 1C2 (no salt mist), 1S2 (sand must not get inside the devices), 1M4<br>2K2, 2C1, 2S1, 2M2 (max. fall height 0.3 m) |
| <b>EMC emitted interference</b>                                                                                                                                                                 | acc. to IEC 60947-4-2: Class A                                                                                                                                                                                                                                                    |

### Communication/ Protocol

|                                                                                                                                                              |                                 |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| <b>communication module is supported</b>                                                                                                                     |                                 |
| <ul style="list-style-type: none"> <li>• PROFINET standard</li> <li>• EtherNet/IP</li> <li>• Modbus RTU</li> <li>• Modbus TCP</li> <li>• PROFIBUS</li> </ul> | Yes<br>Yes<br>Yes<br>Yes<br>Yes |

### UL/CSA ratings

|                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                                                                                        |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>manufacturer's article number</b>                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                                                                        |
| <ul style="list-style-type: none"> <li>• of the fuse               <ul style="list-style-type: none"> <li>— usable for Standard Faults up to 575/600 V according to UL</li> <li>— usable for High Faults up to 575/600 V according to UL</li> <li>— usable for Standard Faults at inside-delta circuit up to 575/600 V according to UL</li> <li>— usable for High Faults at inside-delta circuit up to 575/600 V according to UL</li> </ul> </li> </ul> | Type: Class J / L, max. 1600 A; Iq = 30 kA<br>Type: Class J / L, max. 1200 A; Iq = 100 kA<br>Type: Class J / L, max. 1600 A; Iq = 30 kA<br>Type: Class J / L, max. 1200 A; Iq = 100 kA |
| <b>operating power [hp] for 3-phase motors</b>                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                                                                                                        |
| <ul style="list-style-type: none"> <li>• at 200/208 V at 50 °C rated value</li> <li>• at 220/230 V at 50 °C rated value</li> <li>• at 460/480 V at 50 °C rated value</li> <li>• at 575/600 V at 50 °C rated value</li> <li>• at 200/208 V at inside-delta circuit at 50 °C rated value</li> <li>• at 220/230 V at inside-delta circuit at 50 °C rated</li> </ul>                                                                                        | 150 hp<br>150 hp<br>350 hp<br>450 hp<br>250 hp<br>250 hp                                                                                                                               |

|                                                             |           |
|-------------------------------------------------------------|-----------|
| value                                                       |           |
| • at 460/480 V at inside-delta circuit at 50 °C rated value | 600 hp    |
| • at 575/600 V at inside-delta circuit at 50 °C rated value | 800 hp    |
| <b>contact rating of auxiliary contacts according to UL</b> | R300-B300 |

|                                                                |                                                             |
|----------------------------------------------------------------|-------------------------------------------------------------|
| <b>Safety related data</b>                                     |                                                             |
| <b>protection class IP on the front according to IEC 60529</b> | IP00; IP20 with cover                                       |
| <b>touch protection on the front according to IEC 60529</b>    | finger-safe, for vertical contact from the front with cover |
| <b>electromagnetic compatibility</b>                           | in accordance with IEC 60947-4-2                            |

|                                 |            |
|---------------------------------|------------|
| <b>Certificates/ approvals</b>  |            |
| <b>General Product Approval</b> | <b>EMC</b> |



[Confirmation](#)



|                                  |                          |                          |
|----------------------------------|--------------------------|--------------------------|
| <b>Declaration of Conformity</b> | <b>Test Certificates</b> | <b>Marine / Shipping</b> |
|----------------------------------|--------------------------|--------------------------|



EG-Konf.

[Type Test Certificates/Test Report](#)



LRS

|                          |              |
|--------------------------|--------------|
| <b>Marine / Shipping</b> | <b>other</b> |
|--------------------------|--------------|



[Confirmation](#)

### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5247-2AC15>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5247-2AC15>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5247-2AC15>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RW5247-2AC15&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5247-2AC15&lang=en)

Characteristic: Tripping characteristics, I<sub>t</sub>, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5247-2AC15/char>

Characteristic: Installation altitude

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5247-2AC15&objecttype=14&gridview=view1>

Simulation Tool for Soft Starters (STS)

<https://support.industry.siemens.com/cs/ww/en/view/101494917>

last modified:

4/10/2022

