

## NEMA 5-15R to C14 Computer AC Power Cable - 10A, 125V, 18 AWG, 1 ft. (0.31 m), Black

MODEL NUMBER: P002-001-10A



Computer AC power cable allows you to connect your PC or other device with a NEMA 5-15P plug to a PDU or UPS with a C13 power outlet.

### Features

**Computer AC Power Cable Connects Computers, Monitors and Other Equipment** This computer AC power cable is designed for low-voltage data center, server room or home/office applications. This NEMA 5-15R to C14 cord converts a NEMA 5-15P plug into a C14 connector. You can use it to connect a computer, monitor, printer or other device with a NEMA 5-15P plug to a surge protector, UPS system or PDU with C13 power outlets. You can also connect your C13 printer or monitor to a switched source on your PC, allowing you to turn both devices on and off at the same time. The 1-ft. (0.31 m) length helps reduce cable clutter.

### Highlights

- Recommended for powering computers, printers and other peripherals
- Adds 1-ft. (0.31 m) to your existing power connection to provide flexibility in placing devices
- NEMA 5-15R to C14 extension cord is ideal replacement for worn-out or missing cable
- Can connect a C13 peripheral to a PC's switched source to save energy and free up an outlet on your surge protector or PDU

### Applications

- Connect devices like computers, printers and monitors to a PDU up to 1-ft. (0.31 m) away in your workstation
- Extend an existing power connection up to 1-ft. (0.31 m) to more easily place a device or reach a power source
- Provide a high-quality replacement for a worn-out or missing power cord
- Power your monitor through a switched source on your PC to free up an outlet on your surge protector or PDU

### Package Includes

- P002-001-10A NEMA 5-15R to C14 Computer AC Power Cable, 1-ft. (0.31 m), Black

## Specifications

| OVERVIEW                    |   |
|-----------------------------|---|
| UPC Code                    | 037332180377                                      |
| Device Compatibility        | Computer; Monitor/HDTV; Printer; UPS; PDU; Server |
| Country/Region              | North America                                     |
| INPUT                       |   |
| Maximum Input Amps          | 10  |
| Voltage Compatibility (VAC) | 125   |

| <b>PHYSICAL</b>                      |                             |
|--------------------------------------|-----------------------------|
| Plug Color                           | Black                       |
| Cable Jacket Color                   | Black                       |
| Cable Jacket Material                | PVC                         |
| Cable Jacket Rating                  | VW-1                        |
| Power Cord Jacket Type               | SJT                         |
| Cable Outer Diameter (OD)            | 7.8mm                       |
| Number of Conductors                 | 3                           |
| Wire Gauge (AWG)                     | 18                          |
| Wire Gauge (OD - mm <sup>2</sup> )   | 0.82                        |
| Cable Length (ft.)                   | 1                           |
| Cable Length (m)                     | 0.30                        |
| Shipping Dimensions (hwd / in.)      | 10.00 x 7.10 x 0.10         |
| Shipping Dimensions (hwd / cm)       | 25.40 x 18.03 x 0.25        |
| Shipping Weight (lbs.)               | 0.22                        |
| Shipping Weight (kg)                 | 0.10                        |
| <b>ENVIRONMENTAL</b>                 |                             |
| Operating Temperature Range          | -4° to 140°F (-20° to 60°C) |
| Storage Temperature Range            | -4° to 140°F (-20° to 60°C) |
| Operating Humidity Range             | 10% to 65% RH               |
| Storage Humidity Range               | 10% to 65% RH               |
| <b>CONNECTIONS</b>                   |                             |
| Side A - Connector 1                 | IEC-320-C14                 |
| Side B - Connector 1                 | NEMA 5-15R                  |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                             |
| Antibacterial                        | No                          |
| Angled Plug                          | No                          |
| High Voltage                         | No                          |
| Locking Plug                         | No                          |
| Coiled Power Cord                    | No                          |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                             |
| Product Certifications               | cUL Listed; UL Listed       |



1000 Eaton Boulevard  
Cleveland, OH 44122  
United States

|                                     |                           |
|-------------------------------------|---------------------------|
| Product Compliance                  | RoHS                      |
| <b>WARRANTY &amp; SUPPORT</b>       |                           |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |



© 2023 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.