**OBSOLETE**

SPECIFICATIONS:

MATERIAL:-
PHOSPHOR BRONZE

FINISH:-
TIN PLATED

ELECTRICAL:-

CURRENT RATING: 1A AC/DC

WORKING VOLTAGE: 100V AC/DC

WITHSTAND VOLTAGE: 500V AC/MINUTE

CONTACT RESISTANCE: 20 mΩ MIN.

INSULATION RESISTANCE: 1000 MΩ MIN.

ENVIRONMENTAL:-

TEMPERATURE RANGE: -25°C TO +85°C


OTHERS:-

APPLICABLE WIRE: AWG #28 TO #32


INSULATION OD: 0.90MM MAX.

ACCEPTS: M30-130 XX 00 HOUSING


NOTES: ALL DIMENSIONS AND NOTES
MARKED * ARE CRITICAL AND
MUST BE CHECKED IN ACCORDANCE
WITH QUALITY DOC. QI-02A



SEC: A-A



SEC: B-B



SEC: C-C

Allan HTUT	2 1	02.07.08 14.02.07	A139 -
NAME	ISS.	DATE	C/NOTE
APPROVED:			
CHECKED:	<i>Alan</i>		
DRAWN:	Allan		
CUSTOMER REF.:			
ASSEMBLY DRG:			

HARWIN

HARWIN USA
TEL: 603 893 5376
FAX: 603 893 5396
mis@harwin.com

HARWIN Europe (UK)
TEL: 023 9231 4545
FAX: 023 9231 4590
mis@harwin.co.uk

HARWIN Asia
TEL: +65 6 779 4909
FAX: +65 6 779 3868
mis@harwin.com.sg

THIS DRAWING AND ANY
INFORMATION OR DESCRIPTIVE
MATTER SET OUT HEREON ARE
CONFIDENTIAL AND COPYRIGHT
PROPERTY OF THE HARWIN
GROUP AND MUST NOT BE
DISCLOSED, LOANED, COPIED
OR USED FOR MANUFACTURING,
TENDERING OR FOR ANY
OTHER PURPOSE WITHOUT
THEIR WRITTEN PERMISSION.

TOLERANCES

X. = ±1mm
X.X = ±0.25mm
X.XX = ±0.15mm
X.XXX = ±0.08mm

ANGLES = ±5°
UNLESS STATED

MATERIAL:

SEE NOTES

FINISH:

SEE NOTES

S/AREA:

mm²

TITLE:

1.25MM PITCH CRIMP TERMINAL

DRAWING NUMBER:

M30-3000046

SHT
1
OF
1