

SUMMARY

Wires



Image is for illustrative purpose only

| | |
|------------------|----------------|
| Series | 2B |
| Termination type | |
| IP rating | 50 |
| AWG wire size | 0.00 - 0.00 |
| Cable Ø | 4.30 - 5.20 mm |
| Status | active |

Download

[Request a quote](#)

[Catalog](#)

TECHNICAL DETAILS

Mechanics

| | |
|-------------------|---|
| Shell Style/Model | FG*: B series cable collet |
| Keying | No keying |
| Housing Material | Brass (nickel plated [SAE AMS QQ N 290]) collet |
| Weight | 3.89 g |

Performance

| |
|---------------|
| Configuration |
| Insulator |
| Rated Current |

Others

| |
|---|
| Endurance (Shell): 5000 |
| Temp (min / max): -55° C / +250° C |
| Humidity (max): <=95% [at 60 deg C / 140 F] |
| Vibration: 15 g [10 Hz - 2000 Hz] |
| Shock Resistance: 100 g [6 ms] |

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Climatical Category: 50/175/21
Shielding (min): 75 dB (10 MHz)
Shielding (min): 40 dB (1 GHz)
12NC part number: 4022.438.33585

DRAWINGS



No keying

Dimensions

| | A | B | L |
|-----|------|------|------|
| mm. | 5.2 | 5.2 | 13.5 |
| in. | 0,20 | 0,20 | 0,53 |

RECOMMENDED BY LEMO

Tools

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.