Data sheet 28703.4 KDS-SR-FB3/A BK





Cable entry with moulded-in seal, Mounting type: Screws, Length: 120 mm, Width: 39 mm, IP 66, Colour: Black

RAL: 9005

Business data

| business data | |
|--|-----------------|
| Article number | 28703.4 |
| Article name | KDS-SR-FB3/A BK |
| GTIN (EAN) | 4044211225506 |
| Packaging unit | 10 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 42.2 g |
| Weight per piece (including packaging) | 47.1 g |
| Unit of weight | G |
| Customs number | 39259020 |
| Country of origin | DE |
| Product description | Cable Entry |
| Colour | Black |
| | |

Data sheet



28703.4 KDS-SR-FB3/A BK


| Technical data | | |
|----------------------------------|--------------------------|--|
| Dimensions | | |
| Length | 120 mm | |
| Lenght of wall cutout | 89 mm | |
| Width | 39 mm | |
| Width of wall cutout | 24 mm | |
| Height | 19 mm | |
| Installation height | 18.9 mm | |
| Diameter of the screw holes | 5.5 mm | |
| Materials | | |
| Material | Polyamide 6.6 | |
| Glass-fibre reinforced | ✓ | |
| Flammability class UL 94 | V-0 | |
| Working temperature, min. | -40 °C | |
| Working temperature, max. | 120 °C | |
| Sealing material | TPE | |
| Halogen-free | ✓ | |
| Silicone-free | ✓ | |
| Further technical data | | |
| Mounting type | Screws | |
| Degree of protection | IP66 | |
| Number of screw holes | 2 | |
| Fixing screws | M 5 (ISO 4762 / DIN 912) | |
| Torque of the fixing screws | 3 Nm | |
| Environmental Product Compliance | | |
| REACH Conform | yes | |
| REACH Reference date | 2023-01-17 | |
| REACH Candidate Substance Note | No | |
| RoHS Conform | yes | |

Data sheet 28703.4 KDS-SR-FB3/A BK



Media





Data sheet

28703.4 KDS-SR-FB3/A BK



Accessories

Actuating tool



Using the KDS BW1 actuating tool, the seals can be conveniently mounted in and dismantled from the frame. The ergonomic grip and the special shape enable simple and precise installations, especially for cabling applications in confined spaces., Material: Polyamide

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| 28622.0 | KDS BW 1 | 4044211216597 | 1 ST |

Sheet-metal puncher



Sheet metal puncher for rectangular openings, Dimensions opening: 89 x 24 mm, Maximum wall thickness: 2.0 mm for stainless steel sheet, Material: steel

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|-------------------|
| 28736.0 | BL KDS-FB3 | 4044211221829 | 1 ST |



Sheet metal puncher for rectangular openings, Dimensions opening: 89 x 24 mm, Maximum wall thickness: 2.0 mm for stainless steel sheet, Material: steel

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|---------------|---------------|-------------------|
| <u>28742.0</u> | BL-VA KDS-FB3 | 4044211221966 | 1 ST |

Flat cable seals

Seal, Mounting type: Plug in, Length 86.5 mm, Width: 20.3 mm, IP 66, Colour: Grey

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|-----------------|---------------|----------------|
| 28739.6 | KDS-DE-FB3/C GR | 4044211225735 | 5 ST |

Seal dummy, Mounting type: Plug in, Length 86.5 mm, Width: 20.3 mm, IP 66, Colour: Grey

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|-----------------|---------------|----------------|
| 28725.6 | KDS-DE-FB3/A GR | 4044211221188 | 5 ST |

Data sheet 28703.4 KDS-SR-FB3/A BK



Flat cable seals

Seal, Mounting type: Plug in, Length 86.5 mm, Width: 20.3 mm, IP 66, Colour: Grey



| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|-----------------|---------------|----------------|
| 28726.6 | KDS-DE-FB3/B GR | 4044211221195 | 5 ST |