



**SIPMOS® Small-Signal-Transistor**
**Feature**

- n-channel
- enhancement mode
- Logic level
- $dv/dt$  rated
- Qualified according to AEC Q101
- Halogen-free according to IEC 61249-2-21

**Product Summary**

$V_{DS}^{1)}$	600	V
$R_{DS(on),max}$	45	$\Omega$
$I_D$	0.09	A


**SOT89**


Type	Package	Pb-free	Tape and Reel Information	Marking
BSS225	SOT89	Yes	H6327: 1000PCS/reel	KD

**Maximum ratings, at  $T_j=25\text{ °C}$ , unless otherwise specified**

Parameter	Symbol	Conditions	Value	Unit
Continuous drain current	$I_D$	$T_A=25\text{ °C}$	0.09	A
		$T_A=70\text{ °C}$	0.073	
Pulsed drain current	$I_{D,pulse}$	$T_A=25\text{ °C}$	0.36	
Reverse diode $dv/dt$	$dv/dt$	$I_D=0.09\text{ A}$ , $V_{DS}=480\text{ V}$ , $di/dt=200\text{ A}/\mu\text{s}$ , $T_{j,max}=150\text{ °C}$	6	kV/ $\mu\text{s}$
Gate source voltage	$V_{GS}$		$\pm 20$	V
ESD Class JESD22-A114-HBM			Class 1a	
Power dissipation	$P_{tot}$	$T_A=25\text{ °C}$	1.00	W
Operating and storage temperature	$T_j, T_{stg}$		-55 ... 150	$^{\circ}\text{C}$
IEC climatic category; DIN IEC 68-1			55/150/56	

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	

**Thermal characteristics**

Thermal resistance, junction - minimal footprint	$R_{thJA}$		-	-	125	K/W
--	------------	--	---	---	-----	-----

**Electrical characteristics, at  $T_j=25\text{ °C}$ , unless otherwise specified**
**Static characteristics**

Drain-source breakdown voltage <sup>1)</sup>	$V_{(BR)DSS}$	$V_{GS}=0\text{ V}, I_D=250\text{ }\mu\text{A}$	600	-	-	V
Gate threshold voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}; I_D=94\text{ }\mu\text{A}$	1.3	1.9	2.3	
Drain-source leakage current	$I_{D(off)}$	$V_{DS}=600\text{ V}, V_{GS}=0\text{ V}, T_j=25\text{ °C}$	-	-	0.1	$\mu\text{A}$
		$V_{DS}=600\text{ V}, V_{GS}=0\text{ V}, T_j=150\text{ °C}$	-	-	5	
Gate-source leakage current	$I_{GSS}$	$V_{GS}=20\text{ V}, V_{DS}=0\text{ V}$	-	10	100	nA
Drain-source on-state resistance	$R_{DS(on)}$	$V_{GS}=4.5\text{ V}, I_D=0.09\text{ A}$	-	30	45	$\Omega$
		$V_{GS}=10\text{ V}, I_D=0.09\text{ A}$	-	28	45	
Transconductance	$g_{fs}$	$ V_{DS} >2 I_D R_{DS(on)max}, I_D=0.075\text{ A}$	0.05	0.14	-	S

<sup>1)</sup>  $V_{DS}$  is zero-hour rated, see note at p.8

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	

**Dynamic characteristics**

Input capacitance	$C_{iss}$	$V_{GS}=0\text{ V}, V_{DS}=25\text{ V},$ $f=1\text{ MHz}$	-	99	131	pF
Output capacitance	$C_{oss}$		-	7.6	11	
Reverse transfer capacitance	$C_{rss}$		-	3.1	4.4	
Turn-on delay time	$t_{d(on)}$	$V_{DD}=300\text{ V},$ $V_{GS}=10\text{ V}, I_D=0.09\text{ A},$ $R_G=6\ \Omega$	-	14.0	20.0	ns
Rise time	$t_r$		-	38.0	57.0	
Turn-off delay time	$t_{d(off)}$		-	62.0	93	
Fall time	$t_f$		-	41.0	62	

**Gate Charge Characteristics**


Gate to source charge	$Q_{gs}$	$V_{DD}=400\text{ V},$ $I_D=0.09\text{ A},$ $V_{GS}=0\text{ to }10\text{ V}$	-	0.32	0.43	nC
Gate to drain charge	$Q_{gd}$		-	1.4	2.1	
Gate charge total	$Q_g$		-	3.9	5.8	
Gate plateau voltage	$V_{plateau}$		-	3.3	-	V

**Reverse Diode**

Diode continuous forward current	$I_S$	$T_A=25\text{ }^\circ\text{C}$	-	-	0.09	A
Diode pulse current	$I_{S,pulse}$		-	-	0.36	
Diode forward voltage	$V_{SD}$	$V_{GS}=0\text{ V}, I_F=0.09\text{ A},$ $T_j=25\text{ }^\circ\text{C}$	-	0.75	1.2	V
Reverse recovery time	$t_{rr}$	$V_R=300\text{ V}, I_F=0.09\text{ A},$ $di_F/dt=100\text{ A}/\mu\text{s}$	-	246	370	ns
Reverse recovery charge	$Q_{rr}$		-	248	373	


**1 Power dissipation**

$$P_{\text{tot}} = f(T_A)$$



**2 Drain current**


$$I_D = f(T_A); V_{GS} \geq 10 \text{ V}$$



**3 Safe operating area**

$$I_D = f(V_{DS}); T_A = 25 \text{ °C}; D = 0$$


parameter:  $t_p$



**4 Max. transient thermal impedance**

$$Z_{\text{thJA}} = f(t_p)$$


parameter:  $D = t_p / T$



**5 Typ. output characteristics**

$I_D = f(V_{DS}); T_j = 25\text{ }^\circ\text{C}$


parameter:  $V_{GS}$



**6 Typ. drain-source on resistance**


$R_{DS(on)} = f(I_D); T_j = 25\text{ }^\circ\text{C}$

parameter:  $V_{GS}$




**7 Typ. transfer characteristics**

$I_D = f(V_{GS}); |V_{DS}| > 2|I_D|R_{DS(on)max}$




**8 Typ. forward transconductance**

$g_{fs} = f(I_D); T_j = 25\text{ }^\circ\text{C}$



**9 Drain-source on-state resistance**


$R_{DS(on)} = f(T_j); I_D = 0.1 \text{ A}; V_{GS} = 10 \text{ V}$



**10 Typ. gate threshold voltage**


$V_{GS(th)} = f(T_j); V_{DS} = V_{GS}; I_D = 94 \mu\text{A}$

parameter:  $I_D$



**11 Typ. capacitances**


$C = f(V_{DS}); V_{GS} = 0 \text{ V}; f = 1 \text{ MHz}; T_j = 25^\circ\text{C}$



**12 Forward characteristics of reverse diode**

$I_F = f(V_{SD})$


parameter:  $T_j$



**13 Typ. gate charge**


$$V_{GS} = f(Q_{gate}); I_D = 0.1 \text{ A pulsed}$$

parameter:  $V_{DD}$



**14 Drain-source breakdown voltage**

$$V_{BR(DSS)} = f(T_j); I_D = 250 \mu\text{A}$$







Published by  
Infineon Technologies AG  
81726 Munich, Germany  
© 2008 Infineon Technologies AG  
All Rights Reserved.

#### Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

#### Information

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office ([www.infineon.com](http://www.infineon.com)).

#### Warnings

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office. Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.