HellermannTyton

Specification Sheet

Part Number: 181-93003

A temporary film is applied to the covers to protect against scratches and is writable for identification during installation.

Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.

Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)

Wiring Duct Cover for 3" Duct, 6 ft Long, PVC, Black, 120 ft/carton

Article Number	181-93003
Туре	TC3
Color	Black (BK)
Quantity Per	carton
Product Description	HellermannTyton's Pro-Duct wiring duct covers are sold separately and interchangeable among the 3 styles of duct (solid, slotted and high density). Manufactured from high impact, rigid PVC, Pro-Duct covers come in standard colors of white, gray and black. Wiring duct covers are available in 6 foot lengths.
Short Description	Wiring Duct Cover for 3" Duct, 6 ft Long, PVC, Black, 120 ft/carton

Global Part Name

TC3-PVC-BK

Length L (Imperial)	6.0
Length L (Metric)	1.83
Width W (Imperial)	3.0
Width W (Metric)	76.2
Height H (Imperial)	0.308
Height H (Metric)	7.82

Material	Polyvinylchloride (PVC)	
Material Shortcut	PVC	
Flammability	UL 94 V-0	
Halogen Free	No	
UV Resistant (Yes/No)	No	
Operating Temperature	+122°F (+50°C)	
Reach Compliant (Article 33)	No	
ROHS Compliant	Yes	

Certification/Specification	EN 50085-2-3_1A UL CSA EN 50085-1:2005 + A1:2013		
UL Recognized (US)	Yes		
Package Quantity (Imperial)	120.0		
Package Quantity (Metric)	36.58		
Customs Number	3925900000		

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

Contact Lls	RoHS/WEEE Compliance	Disclaimer	Torms and Conditions
Contact Us		Discialmer	Terms and Conditions