

## Socket strip - SFL (2,8-0,8)F32/ZD - 2285328

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Flat connector socket, Number of positions: 32, Pitch: 0 mm, Connection method: Slip-on connection, Color: green, Contact surface: Tin

The illustration shows the version SFL (2,8-0,8) F 48



### Key commercial data

Packing unit	1 pc
GTIN	 4 017918 055929
Weight per Piece (excluding packing)	35.47 GRM
Custom tariff number	85369010
Country of origin	Poland

### Technical data

#### Dimensions

Length	14.8 mm
Height	28.6 mm
Width	95 mm
Pitch	0 mm
Hole diameter	2.8 mm

#### General

Range of articles	SFL (2,8-0,8)
Insulating material group	II
Rated surge voltage (III/3)	2.5 kV
Nominal cross section	0 mm <sup>2</sup>
Insulating material	PA-F

# Socket strip - SFL (2,8-0,8)F32/ZD - 2285328

## Technical data

### General

Inflammability class according to UL 94	HB
Number of positions	32

## Classifications

### eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260704
eCl@ss 7.0	27440490
eCl@ss 8.0	27440490

### ETIM

ETIM 3.0	EC000516
ETIM 4.0	EC002498
ETIM 5.0	EC000516

### UNSPSC

UNSPSC 6.01	30211810
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

## Approvals

### Approvals

---

Approvals

GOST

---

Ex Approvals

---

Approvals submitted

# Socket strip - SFL (2,8-0,8)F32/ZD - 2285328

## Approvals

### Approval details



## Drawings

Dimensioned drawing



