



Shellsize	A	B	C	D	E	F <sup>+1</sup> <sub>-3</sub>	Cable Ø	Part-NO.
1	40.76	25.00	SW 20	51.0	22.0	77.0	5 - 10	165X15069X
2	49.06	33.30	SW 24	51.0	22.0	79.0	7 - 12	165X15079X
3	62.80	47.04	SW 24	59.5	22.0	87.5	7 - 12	165X15089X
4	78.86	63.50	SW 30	67.0	22.0	99.0	9 - 16	165X15099X
5	76.46	61.10	SW 40	67.0	24.8	107.0	13 - 20	165X15109X

Directive 2002/95 EC  
„RoHS“  
Compliant

- NOTES:
- HOOD: ABS V0, METALLIZED
  - SCREWS: STAINLESS STEEL

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL

CUSTOMER APPROVAL DATE:

NAME: TITLE:

COMPANY NAME:

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH

DO NOT ALTER CAD DRAWING BY HAND

rev.	description	date	name
2 x b	Ä 3353	29.04.2009	Lehmen
a	Origin		

tolerance		dim. in mm	scale:
2006	date	name	1:1
drawn	30.03.	Lehmenkühler	material: SEE NOTES
appd.	30.03.	Mickenbecker	title: WATER RESISTANT D-SUB HOOD 9-50pos. with short screw
norm			dwg no: AutoCAD 2006
d-old			DIN-A 3
CONEC®			sh: 1/1
part no: SEE TABLE			