

In case of consideration for using Autom otive equipm ent/device which dem and high re liability, kindly contactour sales w indow correspondents.

APPLICABLE STANDARD		TEST METHOD		REQUIREMENTS		Q/T	AT
OPERATING TEMPERATURE RANGE	-55 °C TO 85 °C	STORAGE TEMPERATURE RANGE	-10 °C TO 60 °C (3)			X	X
VOLTAGE	100 V AC	OPERATING HUMIDITY RANGE	40 % TO 80 %			X	X
CURRENT	0.4 A	STORAGE HUMIDITY RANGE	40 % TO 70 % (3)			X	X
<b>SPECIFICATIONS</b>							
ITEM	TEST METHOD		REQUIREMENTS		Q/T	AT	
CONSTRUCTION				GENERAL EXAMINATION			
VISUALLY AND BY MEASURING INSTRUMENT.		CONFIRMED VISUALLY.		ACCORDING TO DRAWING.			
<b>ELECTRIC CHARACTERISTICS</b>							
CONTACT RESISTANCE	100 mA (DC OR 1000 Hz),	80 mΩ MAX. (1)	X	-			
CONTACT RESISTANCE MILLIVOLT LEVEL METHOD	20 mV MAX, 1 mA(DC OR 1000Hz)	100 mΩ MAX. (2)	X	-			
INSULATION RESISTANCE	250 V DC.	100 MΩ MIN.	X	-			
VOLTAGE PROOF	300 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	X	-			
<b>MECHANICAL CHARACTERISTICS</b>							
MECHANICAL OPERATION				50 TIMES INSERTIONS AND EXTRACTIONS.			
		① CONTACT RESISTANCE: 100 mΩ MAX. (2)		② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X	-
VIBRATION		FREQUENCY 10 TO 55 Hz, AMPLITUDE : 1.5 mm, AT 2h FOR 3 DIRECTION.		① NO ELECTRICAL DISCONTINUITY OF 1 μs.		X	-
SHOCK		490 m/s <sup>2</sup> , DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.		② CONTACT RESISTANCE: 100 mΩ MAX. (2)		X	-
				③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X	-
<b>ENVIRONMENTAL CHARACTERISTICS</b>							
DAMP HEAT (STEADY STATE)		EXPOSED AT 40±2 °C, 90 ~ 95 %, 96 h.		① CONTACT RESISTANCE: 100 mΩ MAX. (2)		X	-
RAPID CHANGE OF TEMPERATURE		TEMPERATURE:-55 → +15 ~ +35 → +85 → +15 ~ +35 °C TIME 30 → 2 ~ 3 → 30 → 2 ~ 3 min UNDER 5 CYCLES.		② INSULATION RESISTANCE: 100 MΩ MIN.		X	-
CORROSION SALT MIST		EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.		③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X	-
HYDROGEN SULPHIDE		EXPOSED IN 3 PPM FOR 96 h. (TEST STANDARD: JEIDA-38)		① CONTACT RESISTANCE: 100 mΩ MAX. (2)		X	-
RESISTANCE TO SOLDERING HEAT		1) REFLOW SOLDERING: : 250 °C MAX, : 220 °C MIN, FOR 60 s 2) SOLDERING IRONS : 360 °C, FOR 5 s		② NO HEAVY CORROSION.		X	-
SOLDERABILITY		SOLDERED AT SOLDER TEMPERATURE: 240 ± 3 °C, FOR IMMERSION DURATION, 3 s.		NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.		X	-
				A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSERD.		X	-
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE			
Δ							
<b>REMARK</b>							
(1) THIS CONNECTOR'S INITIAL CONTACT RESISTANCE SHALL BE 80 mΩ BECAUSE OF THE BULK RESISTANCE OF STACKING HEIGHT 16 mm TYPE.		APPROVED	HS. OKAWA	06.11.10			
(2) AFTER TEST, THE CHANCE OF THE CONTACT RESISTANCE SHALL BE 20 mΩ MAX.		CHECKED	HS. OZAWA	06.11.09			
(3) THIS STORAGE INDICATES A LONG-TERM STORAGE STATE FOR THE UNUSED PRODUCT BEFORE THE BOARD MOUNTED.		DESIGNED	KY. MAKAMURA	06.11.09			
Unless otherwise specified, refer to JIS C 5402.		DRAWN	SY. KAMIGA	06.11.08			
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-150862-21				
<b>HRS</b>		SPECIFICATION SHEET		PART NO.	FX8C-80P-SV4 (91)		
		HIROSE ELECTRIC CO., LTD.		CODE NO.	CL578-0583-3-91		
							1/1