SIEMENS

Data sheet US2:49SDPB5



Class 49 Pushbutton Kit

| product brand name | Enclosed Control Product Accessories |
|--|--|
| design of the product | Start-Stop Push Buttons |
| product type designation | Pilot device |
| special product feature | For use in enclosures with lift-off cover. |
| General technical data | |
| weight [lb] | 0.4 lb |
| Height x Width x Depth [in] | 3.5 × 1.75 × 3.22 in |
| touch protection against electrical shock | finger-safe |
| ambient temperature [°F] | |
| during storage | -40 +149 °F |
| during operation | -4 +104 °F |
| ambient temperature | |
| during storage | -40 +65 °C |
| during operation | -20 +40 °C |
| country of origin | Mexico |
| accessories / included | Wires, legend holders & legend plates |
| Actuator | |
| diameter | 22 mm |
| design of the actuating element | Flush pushbutton (FOR & REV); Raised pushbutton (STOP) |
| material / of the actuating element | Plastic |
| color / of the actuating element | START = black / STOP = red |
| product function / illumination | No |
| number of switching positions | 2 |
| mechanical service life (operating cycles) / typical | 10 000 000 |
| Contact block | |
| number of NC contacts / for auxiliary contacts | 1 |
| number of NO contacts / for auxiliary contacts | 1 |
| design of the contact / of auxiliary contacts | Silver alloy |
| mechanical service life (operating cycles) / of auxiliary contacts / typical | 10 000 000 |
| electrical endurance (operating cycles) | 10 000 000 |
| Legend | |
| material | Synthetic paper label with adhesive back |
| marking / of inscription plate | ON OFF START STOP JOG |
| color / of inscription plate | Black foreground / White background |
| Mounting/wiring | |
| fastening method | Bracket for use with enclosures with lift-off covers |
| type of electrical connection | screw-type terminals |
| tightening torque [lbf·in] / with screw-type terminals | 7 8 lbf·in |
| type of connectable conductor cross-sections / for AWG cables / for control connection / with screw-type terminals / single or | 2x (18 16 AWG) |

| multi-stranded | | |
|---|------------|--|
| temperature / of the conductor / for control connection / with screw-type terminals / maximum permissible | 75 °C | |
| material / of the conductor | CU | |
| Certificates/ approvals | | |
| certificate of suitability | cULus | |
| Further information | | |
| Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/us/Catalog/product?mlfb=US2:49SDPB5 Service&Support (Manuals, Certificates, Characteristics, FAQs,) https://support.industry.siemens.com/cs/ww/en/ps/US2:49SDPB5 Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros,) http://www.automation.siemens.com/bilddb/cax_us.aspx?mlfb=US2:49SDPB5⟨=en | | |
| last modified: | 3/6/2023 🗹 | |