SIEMENS

Data sheet

US2:52BP7B2XB



30mm BlackMax, Epoxy Coated Corrosion Resistant Complete Metal Unit Illuminated Push-Pull Operator Full Voltage, 6V AC LED Lamp Mushroom Head Cap Small 1 3/4" (44.5 mm) Metal, Black with Red Lens 3 Position Pull-Momentary/Push-Maintained UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

design of the product Actuator round Enclosure 1 delivery state as a kit No Actuator Product extension optional light source Yes material of the actuating element metal mushroom head with plastic lens type of unicking device puil-to-unlatch mechanism number of switching positions 3 Front ring yes product component front ring Yes design of the front ring metal color of the front ring black Holder Intervention material of the holder Metal Contract tooks lampholders 1 socket design BA 9s with LED number of LED modules 1 General technical data product component product component No • light source Yes degree of polition 1 type of voltage AC/DC • of the input vol	-	
number of command points 1 delivery state as a kit No Actuator		Actuator round
delivery state as a kit No Actuator	Enclosure	
Actuator Product extension optional light source Yes material of the actuating element metal mushroom head with plastic lens type of unlocking device pull-b-unlatch mechanism number of switching positions 3 Front ring product component front ring product component front ring Yes design of the front ring standard material of the front ring metal color of the front ring back Holder Metal Contact block/ lampholder standard socket design BA 9s with LED number of LED modules 1 Display metal outce component Yes eilight source Yes degree of pollution 1 type of voltage AC/DC e of the loparting voltage AC/DC e of the loparting voltage AC/DC supply voltage of the light source at AC at 60 Hz #PO e rated value 8 6 V	number of command points	1
product extension optional light source Yes material of the actuating element metal mushroom head with plastic lens type of unlocking device pull-to-unlatch mechanism number of switching positions 3 Front ring Yes design of the front ring metal design of the front ring metal color of the front ring black Holder metal color of the pholder metal socket design number of LED modules number of LED modules 1 General technical data metal product component iegit source iegit source Yes degree of pollution 1 type of voltage AC/DC of the input voltage AC/DC of the input voltage AC/DC	delivery state as a kit	No
material of the actuating element metal mushroom head with plastic lens type of unlocking device pull-to-unlatch mechanism number of switching positions 3 Front ring Yes design of the front ring Yes design of the front ring metal color of the front ring metal color of the front ring metal color of the front ring black Holder metal color of the front ring black Holder metal color of the front ring black Holder Metal Contact block/ lampholder socket design socket design BA 9s with LED number of LED modules 1 General technical data formation product component eight source eight source Yes degree of pollution 1 type of voltage AC/DC e. of the operating voltage AC/DC surge voltage resistance rated value 4kV protoction class IP IP	Actuator	
type of unlocking device pull-to-unlatch mechanism number of switching positions 3 Front ring product component front ring Yes design of the front ring standard metal color of the front ring metal color of the front ring material of the front ring black Holder material of the holder Metal Contact block/ lampholder socket design BA 9s with LED number of lampholders number of lampholders 1 Display number of lampholders 1 Contact data product component • ight source Yes • lamp transformer No • ight source Yes • of the operating voltage AC/DC • • ight source Yes • of the input voltage AC/DC • 1 Yes Y	product extension optional light source	Yes
A 3 Front ring Yes groduct component front ring Standard material of the front ring metal color of the front ring black Holder metal color of the front ring black Holder Metal Contact block/ lampholder Metal Contact block/ lampholder 1 color of the polders 1 Display Inumber of LED modules number of LED modules 1 General technical data Product component • light source Yes degree of pollution 1 type of voltage AC/DC • of the operating voltage AC/DC surge voltage resistance rated value 4 kV protect conges IP IP66 voltage IP20 Supply voltage AC/DC supply voltage of the light source at AC at 60 Hz • rated value • rated value 8 6 V supply voltage of the light source at DC 8 6 V • rated value 8 6 V	material of the actuating element	metal mushroom head with plastic lens
Front ring Yes design of the front ring standard material of the front ring metal color of the front ring metal color of the front ring black Holder Metal Contact black/ lampholder socket design socket design BA 9s with LED number of lampholders 1 Display number of LED modules number of LED modules 1 General technical data Product component • light source Yes degree of pollution 1 type of voltage AC/DC • of the operating voltage AC/DC • of the terminal IP20 Supply voltage Ho68 • of the terminal IP20 Supply voltage of the light source at AC at 60 Hz at 4V • rated value 8 6 V supply voltage of the light source at DC a 6 V • rated value 8 6 V	type of unlocking device	pull-to-unlatch mechanism
product component front ring Yes design of the front ring standard material of the front ring metal color of the front ring black Holder metal color of the front ring black Holder Metal Contact block/ lampholder socket design socket design BA 9s with LED number of lampholders 1 Ofeneral tochnical data product component • light source Yes degree of pollution 1 type of voltage AC/DC • of the operating voltage AC/DC • of the terminal IP20 Supply voltage AC/DC supply voltage AC/DC • of the terminal IP20 Supply voltage AC/DC • of the terminal IP20 Supply voltage AC/DC supply voltage AC/DC • of the terminal IP20 Supply voltage AC/DC • stad value 8 6 V supply voltage of the light source at DC • rated value • rated value 8 6 V	number of switching positions	3
design of the front ring standard material of the front ring black Holder black material of the holder Metal Contact block/ lampholder socket design socket design BA 9s with LED number of lampholders 1 Display	Front ring	
material of the front ring metal color of the front ring black Holder Metal Contact block/ lampholder Socket design socket design BA 9s with LED number of lampholders 1 Display Image: Contact block/ lampholder number of LED modules 1 General technical data Image: Contact block/ lampholder product component Image: Contact block/ lampholder Ight source Yes degree of pollution 1 type of voltage AC/DC • of the operating voltage AC/DC • of the input voltage AC/DC • of the input voltage AC/DC • of the terminal IP20 Supply voltage of the light source AC/DC supply voltage of the light source at AC at 60 Hz * 6 V supply voltage of the light source at DC 8 6 V • rated value 8 6 V	product component front ring	Yes
color of the front ring black Metrial of the holder Metal Contact block/ lampholder socket design socket design BA 9s with LED number of lampholders 1 Display 1 General technical data Forduct component • lamp transformer No • light source Yes degree of pollution 1 type of vitage AC/DC • of the operating voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage of the light source at AC at 60 Hz 8 6 V supply voltage of the light source at DC 8 6 V connections/ Terminals 8 6 V	design of the front ring	standard
Holder Metal Contact block/lampholder socket design BA 9s with LED number of lampholders 1 Display 1 General technical data product component • lamp transformer No • light source Yes degree of pollution 1 type of voltage AC/DC • of the operating voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage AC/DC supply voltage of the light source at AC at 60 Hz • rated value • rated value 8 6 V supply voltage of the light source at DC 8 6 V • rated value 8 6 V	material of the front ring	metal
material of the holder Metal Contact block/ lampholder BA 9s with LED number of lampholders 1 Display 1 number of LED modules 1 General technical data 1 product component Imption Ight source Yes degree of pollution 1 type of voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 IP20 Supply voltage of the light source type of voltage of the light source at AC at 60 Hz AC/DC supply voltage of the light source at DC a 6 V connections/ Terminals S 6 V	color of the front ring	black
Contact block/ lampholder socket design BA 9s with LED number of lampholders 1 Display number of LED modules 1 General technical data product component e light source Yes degree of pollution 1 type of voltage AC/DC e of the operating voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 e of the terminal IP20 Supply voltage of the supply voltage of the light source AC/DC supply voltage of the supply voltage of the light source AC/DC supply voltage of the supply voltage of the light source AC/DC supply voltage of the supply voltage of the light source AC/DC supply voltage of the supply voltage of the light source AC/DC supply voltage of the light source at AC at 60 Hz 8 6 V e rated value 8 6 V connections/ Terminals 8 6 V	Holder	
socket design BA 9s with LED number of lampholders 1 Display 1 number of LED modules 1 General technical data 1 product component 1 • lamp transformer No • light source Yes degree of pollution 1 type of voltage AC/DC • of the operating voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage of the light source at AC at 60 Hz • rated value 8 6 V supply voltage of the light source at DC 8 6 V	material of the holder	Metal
number of lampholders 1 Display 1 number of LED modules 1 General technical data 1 product component 1 • lamp transformer No • light source Yes degree of pollution 1 type of voltage AC/DC • of the operating voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage of the supply voltage of the light source AC/DC supply voltage of the light source at AC at 60 Hz • rated value 8 6 V supply voltage of the light source at DC • rated value 8 6 V	Contact block/ lampholder	
Display number of LED modules 1 General technical data	socket design	BA 9s with LED
number of LED modules 1 General technical data	number of lampholders	1
General technical data product component • lamp transformer No • light source Yes degree of pollution 1 type of voltage • of the operating voltage AC/DC • of the input voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage of the supply voltage of the light source AC/DC supply voltage of the light source at AC at 60 Hz 8 6 V • rated value 8 6 V Connections/Terminals 5 6 V	Display	
product component Iamp transformer No Iamp transformer No Iight source Yes degree of pollution 1 type of voltage 1 of the operating voltage AC/DC of the input voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 of the terminal IP20 Supply voltage AC/DC supply voltage of the light source AC/DC supply voltage of the light source at AC at 60 Hz 8 6 V orated value 8 6 V Connections/Terminals 8 6 V	number of LED modules	1
• lamp transformer No • light source Yes degree of pollution 1 type of voltage AC/DC • of the operating voltage AC/DC • of the input voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage AC/DC supply voltage of the light source at AC at 60 Hz	General technical data	
• light source Yes degree of pollution 1 type of voltage AC/DC • of the operating voltage AC/DC • of the input voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage AC/DC supply voltage of the supply voltage of the light source AC/DC supply voltage of the light source at AC at 60 Hz	product component	
degree of pollution 1 type of voltage AC/DC • of the operating voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage AC/DC supply voltage of the supply voltage of the light source AC/DC supply voltage of the light source at AC at 60 Hz 8 6 V supply voltage of the light source at DC 8 6 V e rated value 8 6 V	lamp transformer	No
type of voltage AC/DC • of the operating voltage AC/DC • of the input voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage type of voltage of the supply voltage of the light source type of voltage of the light source at AC at 60 Hz AC/DC • rated value 8 6 V supply voltage of the light source at DC 8 6 V • rated value 8 6 V	light source	Yes
• of the operating voltage AC/DC • of the input voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage AC/DC supply voltage of the supply voltage of the light source AC/DC supply voltage of the light source at AC at 60 Hz AC/DC • rated value 8 6 V supply voltage of the light source at DC 8 6 V	degree of pollution	1
• of the input voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage type of voltage of the supply voltage of the light source AC/DC supply voltage of the light source at AC at 60 Hz • rated value 8 6 V supply voltage of the light source at DC • rated value 8 6 V	type of voltage	
surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage IP20 supply voltage of the supply voltage of the light source AC/DC supply voltage of the light source at AC at 60 Hz • rated value • rated value 8 6 V supply voltage of the light source at DC • rated value • rated value 8 6 V	 of the operating voltage 	AC/DC
protection class IP IP66 • of the terminal IP20 Supply voltage type of voltage of the supply voltage of the light source AC/DC supply voltage of the light source at AC at 60 Hz • rated value 8 6 V supply voltage of the light source at DC • rated value 8 6 V	 of the input voltage 	AC/DC
• of the terminal IP20 Supply voltage K type of voltage of the supply voltage of the light source AC/DC supply voltage of the light source at AC at 60 Hz 6 V • rated value 8 6 V supply voltage of the light source at DC 8 6 V • rated value 8 6 V	surge voltage resistance rated value	4 kV
Supply voltage type of voltage of the supply voltage of the light source AC/DC supply voltage of the light source at AC at 60 Hz 8 6 V • rated value 8 6 V supply voltage of the light source at DC 8 6 V • rated value 8 6 V	protection class IP	IP66
type of voltage of the supply voltage of the light source AC/DC supply voltage of the light source at AC at 60 Hz 8 6 V • rated value 8 6 V • rated value 8 6 V Connections/ Terminals 8 6 V	• of the terminal	IP20
supply voltage of the light source at AC at 60 Hz • rated value 8 6 V supply voltage of the light source at DC • rated value 8 6 V	Supply voltage	
• rated value 8 6 V supply voltage of the light source at DC • rated value • rated value 8 6 V	type of voltage of the supply voltage of the light source	AC/DC
supply voltage of the light source at DC • rated value 8 6 V	supply voltage of the light source at AC at 60 Hz	
rated value 8 6 V Connections/ Terminals	rated value	8 6 V
Connections/ Terminals	supply voltage of the light source at DC	
	rated value	8 6 V
type of electrical connection screw-type terminals	Connections/ Terminals	

 of modules and accessories 	Screw-type terminal	
tightening torque of the screws in the bracket	20 N·m	
tightening torque [lbf-in] with screw-type terminals	8 8 lbf-in	
Lamp		
type of light source	LED	
color of the light source	red	
Safety related data		
touch protection against electrical shock	finger-safe	
Ambient conditions		
ambient temperature		
during operation	-35 +70 °C	
during storage	-40 +85 °C	
Installation/ mounting/ dimensions		
shape of the installation opening	round	
Certificates/ approvals		
Further information		
Siemens has decided to exit the Russian market (see here). https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business Siemens is working on the renewal of the current EAC certificates. Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus). Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875 Information- and Downloadcenter (Catalogs, Brochures,)		
Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52BP7B2XB Cax online generator http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52BP7B2XB Service&Support (Manuals, Certificates, Characteristics, FAQs,) https://support.industry.siemens.com/cs/ww/en/ps/US2:52BP7B2XB Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros,) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52BP7B2XB⟨=en		

last modified:

5/31/2021 🖸