


HM CONNECTOR

2.5 mm pitch/Wire-to-Wire connectors/Crimp style and Mating style



Introducing a 2.5 mm pitch plug styled wire-to-wire HM connector that supports both HR crimp and HR insulation displacement receptacles which is cost-efficient and highly reliable.

- Supports both HR crimp style and HR insulation displacement receptacles.
- Housing lances
- Panel lock mechanism
- Protective shell-shaped housing.

■ Specifications

- Current rating:
 - Crimp style HR connectors type
3 A AC/DC (AWG #22)
 - Insulation displacement HR connectors type
2 A AC/DC (AWG #24)
- Voltage rating: 250 V AC/DC
Caution: Does not comply with Japan Electrical Appliance and Material Safety Law.
When using, be aware that the exposed contact should not touch or get too close to other metal enclosures, cases and covers.
- Temperature range: -25°C to +85°C
(including temperature rise in applying electrical current)
- Contact resistance:
 - Initial value/ 10 mΩ max.
 - After environmental tests/ 20 mΩ max.
- Insulation resistance: 500 MΩ min.
- Withstanding voltage:
 - There shall be no breakdown or flashover while applying 1,000 VAC for one minute.
- Applicable wire range:
 - Conductor size/ AWG #26 to AWG #22
 - Insulation O.D./ ϕ 1.3 mm to ϕ 1.7 mm
- Applicable panel thickness: 0.8 to 1.6 mm
- * Please refer to the "Handling Precautions for Terminals and Connectors" on our website (listed in the "Technical Documents" column on the Product Information page) before use.
- * RoHS2 compliance
- * Dimensional unit: mm
- * Contact JST for details.



■ Standards

For information on overseas standard registrations, please refer to the "List of Registered Overseas Standards" on our website (listed in the "Technical Documents" column on the Product Information page).

- * Specifications registered to overseas standards may differ from the general specifications listed above.

HM CONNECTOR

Panel layout and Assembly layout




No. of circuits	Model No.	Panel hole dimensions (mm)	
		C	D
2	HMR-02V	3.9	13.3
3	HMR-03V	6.4	15.8
4	HMR-04V	8.9	18.3
8	HMR-08V	18.9	28.3
12	HMR-12V	28.9	38.3


- Note: 1. Drill holes in the panel according to the sketch and table shown above. Burrs must be removed.
 2. The strength of the panel must be considered when punching two or more holes.
 3. The drilled hole must be at the same angle as the direction in which the connector is inserted.

Plug/ HM connector

Contact



Housing



Model No.	Applicable wire range		Q'ty/ reel
	Conductor size AWG (mm ²)	Insulation O.D. (mm)	
SMR-001T-0.6	#26 to #22 (0.13 to 0.33)	1.3 to 1.7	9,000

Material and Surface finish, etc.

Brass, tin-plated

Crimping machine

Contact	Crimping machine	Applicator	Crimp applicator with dies
SMR-001T-0.6	AP-K2N	MKS-L	APLMK SHR/MR001-06

Note: Contact JST for fully automatic crimping applicator.

No. of circuits	Model No.	Dimensions (mm)		Q'ty/bag
		A	B	
2	HMR-02V	2.5	9.3	1,000
3	HMR-03V	5.0	11.8	500
4	HMR-04V	7.5	14.3	500
8	HMR-08V	17.5	24.3	500
12	HMR-12V	27.5	34.3	500

Material and Surface finish, etc.


PA 66

Note: For flame retardant grade of resin material used, please refer to the "List of Registered Overseas Standards" on our website (listed in the "Technical Documents" column on the Product Information page).


HM CONNECTOR

Receptacle / Crimp style HR connector

Contact



Housing



Model No.	Applicable wire range		Q'ty/ reel
	Conductor size AWG (mm ²)	Insulation O.D. (mm)	
SHR-001T-P0.6	#26 to #22 (0.13 to 0.33)	1.3 to 1.7	9,000
Material and Surface finish, etc.			
Phosphor bronze, tin-plated			

Crimping machine


Contact	Crimping machine	Applicator	Crimp applicator with dies
SHR-001T-P0.6	AP-K2N	MKS-L	APLMK SHR/MR001-06

Note: Contact JST for fully automatic crimping applicator.

No. of circuits	Model No.	Dimensions (mm)		Q'ty/bag
		A	B	
2	HRP-02-S	2.5	7.5	2,000
3	HRP-03-S	5.0	10.0	2,000
4	HRP-04-S	7.5	12.5	1,000
8	HRP-08-S	17.5	22.5	500
12	HRP-12-S	27.5	32.5	500
Material and Surface finish, etc.				
PA 66				

Note: For flame retardant grade of resin material used, please refer to the "List of Registered Overseas Standards" on our website (listed in the "Technical Documents" column on the Product Information page).

Receptacle / Insulation displacement HR connector



No. of circuits	Model No.			Dimensions (mm)		Q'ty /bag
	For AWG #28	For AWG #26	For AWG #24	A	B	
2	02HR-8M-P-N	02HR-6S-P-N	02HR-4K-P-N	2.5	7.5	1,000
3	03HR-8M-P-N	03HR-6S-P-N	03HR-4K-P-N	5.0	10.0	1,000
4	04HR-8M-P-N	04HR-6S-P-N	04HR-4K-P-N	7.5	12.5	1,000
8	08HR-8M-P-N	08HR-6S-P-N	08HR-4K-P-N	17.5	22.5	500
12	12HR-8M-P-N	12HR-6S-P-N	12HR-4K-P-N	27.5	32.5	500

Material and Surface finish, etc.

Contact: Copper alloy, tin-plated
Housing: PA 66

Note: For flame retardant grade of resin material used, please refer to the "List of Registered Overseas Standards" on our website (listed in the "Technical Documents" column on the Product Information page).

Applicable wire

UL style No.	Conductor			Insulation O.D. (mm)
	Material and Surface finish, etc.	Size AWG	Composition	
1007	Annealed copper, tin-plated	#28, #26, #24	7 conductors	1.0 to 1.5

Note: Please contact JST for the application of other wires, such as UL style No.