

EVAPOWAY™ TUBULAR CONDENSATE EVAPORATOR PANS

NEW!

Features & Benefits

- ▶ Runs independent of ambient conditions
- ▶ High-limit safety and float-switch operation
- ▶ Tubular-style heating element
- ▶ For use in non low flashpoint refrigerant applications
- ▶ Provides the required heat in the application to eliminate condensation water in commercial refrigeration, HVAC, and vertical transportation (elevators)
- ▶ Space-saving design
- ▶ Wide variety of sizes to accommodate different capacities and voltages



UL US
UL No: SA4508

Specifications

Power Cord: 36 in (914 mm) long

- 120 VAC includes standard 3-prong plug (NEMA 5-15)
- 208 and 240 VAC has bare wire leads
- Other lengths and terminations available upon request

Pan Construction: Corrosion resistant 22-gauge stainless steel

Pan Size: Wide range of choices

Voltage: 120, 208, or 240 VAC

Wattage: 200 to 3000 watts

Dissipation Rate Options: 1.5 to 24 gallons per day (5.7 to 90.8 liters per day)

Ordering Information

Part No.	Nominal Pan Size L x W x H in (mm)	Nominal Assembly Size L x W x H in (mm)	Capacity qt (l)	Watts	Volts	Amps	Maximum Dissipation Rate gal (l) per day
DM02T-1S				200	120	1.67	1.5 (5.7)
DM04T-1S	10 x 7 x 2.5	10.3 x 7 x 5.3	1.75 (1.7)	400	120	3.33	3.5 (13.2)
DM04T-2S	(254 x 178 x 64)	(262 x 178 x 135)		400	208	1.92	3.5 (13.2)
DM04T-3S				400	240	1.66	3.5 (13.2)
DM06S-1S				600	120	5.00	4.5 (17.0)
DM08S-1S	13 x 7 x 2.5	13 x 7 x 5.3	2.37 (2.2)	800	120	6.67	6 (22.7)
DM08S-2S	(330 x 178 x 64)	(330 x 178 x 135)		800	208	3.85	6 (22.7)
DM08S-3S				800	240	3.33	6 (22.7)
DM06M-1S				600	120	5.00	4.5 (17.0)
DM07M-1S				750	120	6.25	5.5 (20.8)
DM07M-2S	13 x 7 x 4	13 x 7 x 6.8	4	750	208	3.61	5.5 (20.8)
DM10M-1S	(330 x 178 x 102)	(330 x 178 x 173)	(3.8)	1000	120	8.33	8 (30.3)
DM10M-2S				1000	208	4.81	8 (30.3)
DM10M-3S				1000	240	4.17	8 (30.3)
DM08WS-1S				800	120	6.67	6 (22.7)
DM08WS-2S	13 x 10 x 2.5	13 x 10.3 x 5.3	4.3 (4.1)	800	208	3.85	6 (22.7)
DM08WS-3S	(330 x 254 x 64)	(330 x 262 x 135)		800	240	3.33	6 (22.7)

Part No. Cross References

BriskHeat Part No.	Supco® Part No.	Birmingham Part No.
DM04T-1S	CP801	840111
DM08S-1S	CP802	880111
DM10M-1S	CP804	810134
DM10M-3S	CP804-240	-
DM10W-1D	CP804HD	810114
DM10W-3D	CP804HD-240	-
DM10W-1S	CP807	-
DM10W-3S	CP807-240	810244
DM10WW-1D	CP808	-
DM15WW-1D	CP815	815134
DM15WW-3D	CP815-240	815244
DM05W-1D	CP816	850114
DM10W-2D	CP817	810214
DM10W-2S	CP818	-
DM15W-1D	CP819	815144
DM15W-2D	CP820	815214
DM15WW-2D	CP821	815234

Ordering Information

Part No.	Nominal Pan Size L x W x H in (mm)	Nominal Assembly Size L x W x H in (mm)	Capacity qt (l)	Watts	Volts	Amps	Maximum Dissipation Rate gal (l) per day
DM05W-1D				500	120	4.17	5 (18.9)
DM06W-1S				600	120	5	4.5 (17.0)
DM07W-1S				750	120	6.25	5.5 (20.8)
DM08W-1S				800	120	6.67	6 (22.7)
DM09W-1S				900	120	3.85	7 (26.5)
DM10W-1S				1000	120	8.33	8 (30.3)
DM10W-2S				1000	208	6.67	8 (30.3)
DM10W-3S				1000	240	7.50	8 (30.3)
DM10W-1D				1000	120	8.33	8 (30.3)
DM10W-2D				1000	208	4.81	8 (30.3)
DM10W-3D	13 x 10 x 4 (330 x 254 x 102)	13 x 10.3 x 6.8 (330 x 262 x 173)	7 (6.6)	1000	240	4.17	8 (30.3)
DM12W-1D				1200	120	10.00	10 (37.9)
DM15W-1S				1500	120	12.5	12 (45.4)
DM15W-2S				1500	208	7.21	12 (45.4)
DM15W-3S				1500	240	6.25	12 (45.4)
DM15W-1D				1500	120	12.5	12 (45.4)
DM015W-2D				1500	208	7.21	12 (45.4)
DM15W-3D				1500	240	6.25	12 (45.4)
DM18W-1D				1800	120	15.00	14 (53.0)
DM20W-2D				2000	208	9.61	15 (56.8)
DM20W-3D				2000	240	8.33	15 (56.8)
DM15X-3S	13 x 10 x 6 (330 x 254 x 152)	13 x 10.3 x 8.8 (330 x 262 x 224)	10 (9.5)	1500	240	6.25	12 (45.4)
DM18X-1D				1800	120	15.00	14 (53.0)
DM15XY-2S	21 x 6 x 6 (533 x 152 x 152)	21 x 6.3 x 8.8 (533 x 160 x 224)	9 (8.5)	1500	208	7.21	12 (45.4)
DM15XY-3S				1500	240	6.25	12 (45.4)
DM05WW-1D				500	120	4.17	5 (18.9)
DM10WW-1D				1000	120	8.33	8 (30.3)
DM10WW-2D				1000	208	4.81	8 (30.3)
DM10WW-3D				1000	240	4.17	8 (30.3)
DM12WW-1D				1200	120	10.00	10 (37.9)
DM15WW-1D				1500	120	12.5	12 (45.4)
DM15WW-2D	21 x 13 x 4 (533 x 330 x 102)	21 x 13 x 6.8 (533 x 330 x 173)	15 (14.2)	1500	208	7.21	12 (45.4)
DM15WW-3D				1500	240	6.25	12 (45.4)
DM18WW-1D				1800	120	15.00	14 (53.0)
DM20WW-2D				2000	208	9.62	15 (56.8)
DM20WW-3D				2000	240	8.33	15 (56.8)
DM30WW-1S				3000 (2 X 1500)	120	12.5	24 (90.8)
DM30WW-3S				3000 (2 X 1500)	240	6.25	24 (90.8)
DM15XX-3S				1500	240	6.25	12 (45.4)
DM18XX-1D	21 x 13 x 6 (533 x 330 x 152)	21 x 13 x 8.8 (533 x 330 x 224)	21 (19.9)	1800	120	15.00	14 (53)
DM30XX-2S				3000 (2 X 1500)	208	7.21	24 (90.8)
DM30XX-3S				3000 (2 X 1500)	240	6.25	24 (90.8)

Accessories

Part No.	Description
A-450-313	Small Float for Evapoway Tubular Pans. Fits pan sizes T, S, WS, and WWS
A-450-314	Large Float for Evapoway Tubular Pans. Fits Pan Sizes M, W, and WW
A-450-315XL	Extra-Large Float for Evapoway Tubular Pans. Fits pan sizes X, XX, and XY