

## Universal Reversible USB 2.0 Cable (Reversible A to B M/M), 6 ft. (1.83 m)

MODEL NUMBER: UR022-006



Reversible USB "A" connector plugs in any direction

### Features

- 6ft, USB 2.0 A-Male to B-Male, with Universal / Reversible "A" connector
- USB 2.0 compliant, to 480Mbps transfer rates
- Backward compatible with previous USB generations
- Gold plated contacts and molded ends provide a lifetime of use
- 28AWG Data Pair, 24AWG Power pair

## Specifications

| OVERVIEW                        |                      |
|---------------------------------|----------------------|
| UPC Code                        | 037332179449         |
| Technology                      | USB 2.0 (High Speed) |
| Cable Type                      | Passive              |
| PHYSICAL                        |                      |
| Cable Jacket Color              | Black                |
| Cable Length (ft.)              | 6                    |
| Cable Length (m)                | 1.83                 |
| Shipping Dimensions (hwd / in.) | 7.00 x 9.00 x 0.50   |
| Shipping Dimensions (hwd / cm)  | 17.78 x 22.86 x 1.27 |
| Shipping Weight (lbs.)          | 0.14                 |

### Highlights

- 6-ft. (1.83 m), USB 2.0, A/B Peripheral device cable
- Universal, Reversible "A" connector allows plugging in any direction

### System Requirements

- Any USB device requiring a USB cable
- USB2.0 performance only when used with USB2.0 device and USB2.0 controller

### Package Includes

- Universal Reversible USB 2.0 A-Male to B-Male Device Cable - 6-ft. (1.83 m)

|                                     |                              |
|-------------------------------------|------------------------------|
| Shipping Weight (kg)                | 0.06                         |
| <b>ENVIRONMENTAL</b>                |                              |
| Operating Temperature Range         | 14° to 122°F (-10° to 50°C)  |
| Storage Temperature Range           | 5° to 140°F (-15° to 60°C)   |
| Operating Humidity Range            | 0% to 90% RH, Non-Condensing |
| Storage Humidity Range              | 0% to 90% RH, Non-Condensing |
| <b>CONNECTIONS</b>                  |                              |
| Side A - Connector 1                | REVERSIBLE USB A (MALE)      |
| Side B - Connector 1                | USB B (MALE)                 |
| Connector Style                     | Straight                     |
| <b>STANDARDS &amp; COMPLIANCE</b>   |                              |
| Product Compliance                  | RoHS                         |
| <b>WARRANTY &amp; SUPPORT</b>       |                              |
| Product Warranty Period (Worldwide) | Lifetime limited warranty    |