

APPLICATOR PARTS LIST

TYPE

Lengthwise

TAPER  
PIN

AMP INCORPORATED  
HARRISBURG, PENNA.

NO.	DESCRIPTION	REQ.	PART NO.	NO.	DESCRIPTION	REQ.	PART NO.	
1	WIRE CRIMPER 1-456406-6	1	<del>471240</del>	42				
2	INS. CRIMPER	1	374878	43	<del>Strip Retainer</del>		<del>471240</del>	
3	ANVIL	1	379096	44	STRIP HOLD DOWN	1	375825	
4	ANVIL SPACER			45				
5	SHEAR BLADE	1	373290	46				
6	REAR SHEAR PLATE 385013-4	1	<del>371311</del>	47				
7	SHEAR BLADE SPACER	2	373072	48				
8	FRONT SHEAR PLATE	1	472529-7	49				
9	REAR ANVIL SPACER PLT.	1	372381	50				
10	FRONT ANVIL SPACER PLT.			51				
11	TOOL SPACER	1	370700	52				
12	CRIMP SPACER	1	370873	53				
13	FRONT STRIP GUIDE	1	371638	54				
14	REAR STRIP GUIDE	1	371638	55				
15	RAM	1	471911	56				
16	TOOL HOLDER	1		57				
17	ADJ. CRIMP MOUNT ASSY.	1	465392-1	58				
18	ADJ. BLOCK			59				
19	APPLICATOR MOUNT	1	570656	60				
20	BASE PLATE			61				
21	BASE BLOCK			62				
22	STRIP GUIDE PLATE			63				
23	ANVIL HOLDER	1	370526	64				
24	AUX. ANVIL HOLDER	1	377515	65	TEN. ADJ. PLATE	1	374999	
25	STRIPPER	1	810872-1	66	MISCELLANEOUS			
26	STRIPPER MOUNT	1	370660	67				
27	RETAINER PLATE	1	372251	68				
28	STRIPPER MOUNT BRACKET			69				
29	STRIPPER BUSHING			70	SCREW, DRIVE #4 x .25	3	21017-6	
30	STOCK DRAG	1	375381	71	PLATE, IDENTIFICATION	1	452373-1	
31	STOCK DRAG HANDLE			72	MECH FEED ASSY	1	692110-2	
32	STOCK DRAG STUD	2	354045-1	REV.	REVISION RECORD	DATE	BY	ECN
33	STOCK DRAG SPRING 1-23847-1	2	<del>370795</del>	E	RETYPED ITEM 39 W/AS 377106	11-9-65	RAC	
34	STOCK DRAG ADJ. SCREW	2	372997	F	REV PER ECN	9-5-68	PB	L-6107
35	FEED FINGER HOLDER			G	REV PER ECN	7-28-68	BP	L-6851
36	FEED FINGER	1	375093	H	REV PER ECN	2-11-70	ES	L-7979
37	FEED FINGER TIP			J	REV MEM #1	7-1-71	IM	L-8382
38	FEED FINGER SPACER			K	REV. PER ECN	3-14-73	DPS	L-9557
39	BASE CASTING	1	570238	L	REV ITEM 6	5-80	BAE	B3550
40	GUARD 457664-1	1	<del>471694</del>	M	ECN R5922	10-10-84	DW	
41				N	ECN A-395872	9-92	no TB	
				P	0150-6588-96	1/96	TB	

CRIMPING DATA			TERMINALS
TO APPLY TERMINAL			42089
			42147
WIRE SIZE	CRIMP HEIGHT	COMMON CRIMP HEIGHT	
18		2.058	
16		3	
CRIMP	SIZE	TYPE	FEED
WIRE	.090	F	
INSUL.	.140	0	.770
SLEEVED			
INSULATION RANGE	WIRE RANGE		
.101 - .120	18-16		
.080 - .120			
EXPLODED VIEW			
A-6000		A-6000-3	
REMARKS:			
THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INC. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.			
■ DENOTES WEARING PARTS RECOMMEND PURCHASE REPLACEMENT			
THIS APPLICATOR IS TO BE USED ON AMP-O-LECTRIC 1-471273-3			
ALIGN. GAGE 679597-1			DIST. 4
SERIAL NO.	DATE SHIPPED	DESIGNED R. Bennett 3-27-63	
CUSTOMER NAME AND ADDRESS			CHK'D. N.T. 3-27-62
APPLICATOR NUMBER			APP'D. DW 3-27-63
REV. IP	671937	SHEET 1 OF	

M