

# AR884CHLT



Sample image

**Order symbol:** AR884CHLT

**Product nbr:** 8561093

**Description:** PC Enclosure

**Remarks:** Hinged transparent cover w/Plastic quick release latch

**EAN:** 6418074067333

**El. number:**

- Finland:
- Denmark:
- Sweden:

**Including:** Hinged cover. Base with 10-32 brass inserts, latched cover with formed in place PUR gasket, stainless hinge pin. Quick release latches. Enclosure mounting foot kit. Accessory 10-32 screws for panel mounting.

ARCA-8x8\_combi

<b>Dimensions:</b>	<b>Height</b>	<b>Width</b>	<b>Depth</b>
mm:	203	203	102
inch:	8	8	4

#### **Materials:**

Material:	Polycarbonate
Base colour:	RAL 7035 -light grey
Cover colour:	Transparent
Gasket material:	Polyurethane

#### **Temperatures:**

Temperature °C (short term)::	-40 ... 140
Temperature °C (continuous):	-40 ... 80
Temperature °F (short term):	-40 ... 250
Temperature °F (continuous):	-40 ... 175

#### **Accessories:**

ALBP88	Aluminum Back Panel (175 x 175)
ABP88	Painted Steel Back Panel (175 x175)
ASP88	Aluminum Swing Panel (204.4 x 204.5 x 0)
ASPHK8	Swing Panel Kit w/o Panel
APBP88	PVC Back Panel (175 x 175)
ADFP88	Dead Front Panel w/ screws (175 x 175 x 0)
ASPK88	Swing Panel Kit incl. Panel
AMFL8	8" Mounting Flange Set

#### **Rating:**

Ingress protection (EN 60529):	IP66; IP67;
Impact Resistance (EN 62262):	IK09;
Electrical insulation:	Not insulated
Halogen free (DIN/VDE 0472, Part 815):	1
UV resistance:	UL 508
Flammability Rating:	UL 508
Glow Wire Test (IEC 695-2-1) °C:	960 °C

NEMA Class

NEMA 4, 4X, 6, 6P, 12, 12K  
and 13

**Certificates:**

ARCA\_CertificateofCompliance