








Write-On Labels on Cards



Material Chart

| Material | Print Method | Temperature Range | Features |
|-------------|--------------|-----------------------------------|--|
| Vinyl Cloth | Pre-Printed | -50°F to 170°F (-46°C to 77°C) | Indoor/outdoor rated; conformable material with repositionable adhesive allows label to be removed and reused or used in temporary applications; provides durability, high temperature resistance, and dimensional stability for rough or textured surfaces. |

| Part Number | Symbol | Description | Width | | Height | | Markers Per Card | Std. Pkg. Card(s) | Std. Ctn. Card(s) |
|-------------|---|-------------|-------|-------|--------|-------|------------------|-------------------|-------------------|
| | | | In. | mm | In. | mm | | | |
| PCWL-BL |  | BLANK | | | | | | 25 | 100 |
| PCWL-ACC |  | ACCEPTED | | | | | | 25 | 100 |
| PCWL-CAL |  | CALIBRATION | | | | | | 25 | 100 |
| PCWL-CALD |  | CALIBRATED | 1.50 | 38.10 | 0.63 | 15.90 | 14 | 25 | 100 |
| PCWL-ICAL |  | CALIBRATION | | | | | | 25 | 100 |
| PCWL-REJ |  | REJECTED | | | | | | 25 | 100 |

Order number of cards required.
Can be clearly identified with Panduit permanent marking pens.

A.
System
Overview

B1.
Cable Ties

B2.
Cable
Accessories

B3.
Stainless
Steel Ties

C1.
Wiring
Duct

C2.
Surface
Raceway

C3.
Abrasion
Protection

C4.
Cable
Management

D1.
Terminals

D2.
Power
Connectors

D3.
Grounding
Connectors

E1.
Labeling
Systems

E2.
Labels

E3.
Pre-Printed
& Write-On
Markers

E4.
Permanent
Identification

E5.
Lockout/
Tagout
& Safety
Solutions

F.
Index