3 INCHES LENGTH



Connector A 132245 SMA Jack Right Angle Bulkhead - Rear Mount Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot Connector B 262121 MMCX Jack Straight Bulkhead - Rear Mount Brass Gold + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

| Right Angle Connector | | Cable | | | Connector B | | | |
|---|---|---|---|---|--|--|---|--|
| 90° 180° 225° 270° 315° 270° D-Flat Bulkhead | Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting: | 132245 SMA R/A BHD Jk 500 SMA Jack Right Angle Solder Standard 50 Ohm Bulkhead - Rear I Brass Gold None Beryllium Copper Gold 12.4 GHz SMA Jack Right A | | Part #: Description: Dielectric: Shielding: Diameter: Impedance: Sheathing: Testing: Length: | RG-174 RG-174 - PE 0.1 PE Braid 0.1 50 Ohm None Continuity Hi-Pot 3 Inches | Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Material: Body Finish: IP Rating: Contact Material: Contact Tinish: Max. Freq.: Booting: Clocking: | 262121 MMCX BHD JK RG MMCX Jack Straight Solder Standard 50 Ohm Bulkhead - Rear Mo Brass Gold None Beryllium Copper Gold 6 GHz MMCX Jack Straigh 0° | |
| Amphenol CUSTOM CABLE CONTROLLED DOCUMENT DO NOT CODY | | | PROPRIETARY INFORMATION A FOR ANY PURPOSE DETRIMEN INC. IT MAY NOT BE REPRODU IN ANY FORM WITHOUT THE W CUSTOM CABLE INC. ACCEPTA | IS DRAWING MAY CONTAIN PATENTED OR OPRIETARY INFORMATION AND MUST NOT BE USED R ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE C. IT MAY NOT BE REPRODUCED OR TRANSCRIBED ANY FORM WITHOUT THE WRITTEN CONSENT OF STOM CABLE INC. ACCEPTANCE OF THIS DRAWING TABLISHES AND AGREEMENT OF THE FOREGOING. | | Title: SMA-RA-JK/MMCX-ST-JK G174 31 Part No: Q-2P01100030031 | | UNLESS SPECIFIED TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES |