

0.75 METER LENGTH




Connector A
132191
SMA Jack Straight
Bulkhead - Rear Mount Brass Gold + Heatshrink

50 Ohm RG-142
Continuity/Hi-Pot

Connector B
142203
SMB Plug Right Angle
Brass Gold + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink
Assembly shall be built with SN96.5 LEAD FREE solder.
See Routing Notes for additional assembly & testing instructions.



Connector A	Cable	Connector B
Part #: 132191 Description: SMA BHD JK RG55 RG142 RG223 500 Type: SMA Gender: Jack Body Type: Straight Contact Type: Solder Polarity: Standard Impedance: 50 Ohm Mounting: Bulkhead - Rear Mount Body Material: Brass Body Finish: Gold IP Rating: None Contact Material: Beryllium Copper Contact Finish: Gold Max. Freq.: 12.4 GHz Booting: SMA Jack Straight BHD	Part #: RG-142 Description: RG-142 - ST 0.195 Dielectric: ST Shielding: Braid Diameter: 0.195 Impedance: 50 Ohm Sheathing: None Testing: Continuity Hi-Pot Length: 0.75 Meter	Part #: 142203 Description: SMB PLUG RG55 RG142 RG223 500 Type: SMB Gender: Plug Body Type: Right Angle Contact Type: Solder Polarity: Standard Impedance: 50 Ohm Mounting: Cable Body Material: Brass Body Finish: Gold IP Rating: None Contact Material: Beryllium Copper Contact Finish: Gold Max. Freq.: 4 GHz Booting: SMB Plug Right Angle Clocking: 0°



CONTROLLED DOCUMENT - DO NOT COPY

THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.

Title:
SMA-ST-JK/SMB-RA-PL G142 0.75M

Part No:
Q-3103V000H.75M

UNLESS SPECIFIED
TOLERANCE:
0-18 inches +/- 1/2"
over 18" +/- 2%
ASSEMBLY:
CENTER LABEL IF LENGTH
IS LESS THAN 12 INCHES