CRYSTAL CLOCK OSCILLATORS

ACPEL





> FEATURES:

- Low jitter PECL logic
- Tight overall frequency stability
- Fast rise and fall times
- Complementary output
- Wide frequency range.


> APPLICATIONS:

- · Gigabit ethernet
- Data telecommunications and networking
- xDSL, Stratum IV
- SONET/SDH

STANDARD SPECIFICATIONS:

PARAMETERS	
ABRACON P/N	ACPEL Series
Frequency	0.75 MHz - 800 MHz
Operating Temperature	0°C to +70°C (see options)
Storage Temperature	-55°C to +125°C
Frequency Stability	± 100 ppm max. (see options)
Supply Voltage (Vdd)	3.3Vdc ±5%
Supply Current	60 mA max. @100MHz
Symmetry	40/60% max.
Rise and Fall Times (Tr/ Tf)	1 ns max. @ 20~80 <mark>%Vpp</mark>
Output Type	PECL square wave
Output Load	50Ω @Vcc -2Vdc
Aging	± 3.0ppm max./ year

OPTIONS AND PART IDENTIFICATION:








CRYSTAL CLOCK OSCILLATORS


ACPEL





OUTLINE DRAWING:





PIN	FUNCTION
1	NC or Comp output
7	GND
8	Output
14	Vcc

Note: Recommend using an approximately 0.01uF bypass capacitor between Pin 7 and 14.

Dimensions: inch (mm)

ATTENTION: Abracon Corporation's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependant Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon Corporation is required. Please contact Abracon Corporation for more information.



