

## Plug-in card block - SKBI 128-C32/C32 - 2270032

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Plug-in card block, Pitch: 0 mm, Connection method: Screw connection, Contact surface: Tin

The illustration shows the version SKBI 128-B 32/B 32



### Key commercial data

Packing unit	1 pc
GTIN	 4 017918 054052
Weight per Piece (excluding packing)	451.9 GRM
Custom tariff number	85369010
Country of origin	Germany

### Technical data

#### Dimensions

Length	66 mm
Height	162 mm
Width	252.4 mm
Pitch	0 mm
Hole diameter	4.2 mm

#### General

Range of articles	SKBI 128
Connection in acc. with standard	EN-VDE
Nominal current $I_N$	current values are defined by the connectors used
Nominal voltage $U_N$	voltage values are defined by the connectors used
Nominal cross section	2.5 mm <sup>2</sup>

## Plug-in card block - SKBI 128-C32/C32 - 2270032

### Technical data

#### General

Stripping length	8 mm
Screw thread	M3
Tightening torque, min	0.5 Nm
Tightening torque max	0.6 Nm

#### Connection data

Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	4 mm <sup>2</sup>
Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Conductor cross section stranded max.	2.5 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12

### Classifications

#### eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260710
eCl@ss 7.0	27141152
eCl@ss 8.0	27141152

#### ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002642
ETIM 5.0	EC002780

#### UNSPSC

UNSPSC 6.01	30211810
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

### Approvals

#### Approvals

## Plug-in card block - SKBI 128-C32/C32 - 2270032

### Approvals

---

Approvals

GOST / GOST

---

Ex Approvals

---

Approvals submitted

---

### Approval details

GOST 

GOST 

### Drawings

# Plug-in card block - SKBI 128-C32/C32 - 2270032

Dimensioned drawing

