



FEATURES:

- ✓ Provides a quick and easy means of shorting two inputs of a miniature double banana jack.
- ✓ The plug to plug and jack to jack dimension is .500" (12,70mm) which is typical for double miniature banana plugs/jacks.
- ✓ ABS body provides insulation protection to the user.
- ✓ Shorting adapter has double miniature jacks at the topside for stacking capability.

MATERIALS:

Miniature Double Banana Jack
 Body: Gold Plated Brass

Miniature Double Banana Plug
 Body: Gold Plated Brass
 Spring: Gold Plated Beryllium Copper

Insulation: ABS molded to banana plug and jack bodies

RATINGS:

Operating Voltage: Hands free usage in controlled voltage environments: 2500 Vrms maximum. *For CE compliance:* not intended for hand-held use at voltages above 33 Vrms/70 Vdc.

Current: 5 Amperes
 Operating Temperature: +122°F (+50°C) Max.

ORDERING INFORMATION:

Model 2035-0 (Black)
 Model 2035-2 (Red)

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).
 All specifications are to the latest revisions. Specifications are subject to change without notice.
 Registered trademarks are the property of their respective companies.

Sales: 800-490-2361 Fax: 888-403-3360 Technical Support: 800-241-2060 (technicalsupport@pomonatest.com)
 For "Where to Buy" information, visit the Pomona web site at www.pomonaelectronics.com