

RECOMMENDER PCB LAYOUT

DIMENSION

L	Nx7.5
P	(N-1)x7.5

N=Number of poles

Poles	Tolerance	
	DIM L	DIM P
2p-6p	±0.15	±0.10
7p-12p	±0.20	±0.20
13p-18p	±0.30	±0.25
19p-24p	±0.40	±0.30


Material

- ① Terminal body(Contact pin):Brass
- ② Wire guard: Stainless steel
- ③ Surface of solder tail: Tin plated
- ④ Insulator(housing): Thermoplastic (UL94V-0), GREEN(RAL6018/T)

Electrical

cULus/VDE
 Voltage rating: 300VAC/450VAC
 Current rating: 10A/10A
 Wire range:0.75-1.5mm²
 Solid wire(AWG): 14-24
 Stranded wire(AWG): 14-24
 Pull force:

Screw:
 Wire strip length: 9-10mm
 Withstanding Voltage: 1.6KV/2.5KV
 Operating temperature: -40°C to +115°C
 Soldering temperature: 250°C±10°C/5 Sec
 Safety Approval:



RoHS compliant
 Unit: mm

Scale	Free		
TOLERANCE		Date	Name
X.	±0.50	19.04.2010	Alex
X.X	±0.30	Approved	19.04.2016 Winnie
X.XX	±0.10	Add the UL File No.	
DIM	TOL	Update	
X.°	±1°	Drawn	
Angle	TOL	Modification	



Customer-No. ASSMANN WSW-No. A-TB750-HAXXH

Drawing-No. ASS 4126 CO rev02

Replace Sheet

1	2	3	4	5	6	7	A
1	2	3	4	5	6	7	H