

Main

Base plate style	Style C
Device Application	Standard mill switch Universal mill switch Heavy duty
Device short name	T
Series name	Severe duty

Complementary

[Ith] conventional free air thermal current	20 A
[Ui] rated insulation voltage	600 V
AWG gauge	AWG 22...AWG 12
Body material	Cast zinc
Cable entry	0.5 in (12.70 mm) NPT conduit entry
Contact code designation	P600 A600
Contacts material	Silver flashed copper
Contact operation	Snap action
Maximum displacement angle	90 °
Positive opening	Without
Stage of operation	Contact closed
Switch actuation	CW and CCW
Tilting angle	45 °
Torque Value	8 lbf.in (0.90 N.m)
Tripping angle	0 °

Environment

Ambient Air Temperature for Operation	-10...185 °F (-23...85 °C)
Electrical shock protection class	Class 0
IP Degree of Protection	IP66 IP67 IP65
NEMA Degree of Protection	NEMA 1/2/4/12/13
Product Certifications	UL Listed CSA CE
Protective treatment	Corrosion resistant gray paint
Shock resistance	30 gn

Ordering and shipping details

Category	21497-9007 FT,T OILTIGHT AND FOUNDRY
Discount Schedule	DS1
GTIN	785901808961
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.99 in (17.742 cm)
Package 1 Width	2.75 in (6.985 cm)
Package 1 Length	17.74 in (45.064 cm)
Package 1 Weight	2.50 lb(US) (1.134 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------