

## USB 3.2 Gen 1 SuperSpeed Device Cable (A to B M/M), 15 ft. (4.57 m)

MODEL NUMBER: U322-015



Allows connection between USB 3.2 Gen 1 Computers to USB 3.2 Gen 1 enabled Peripherals

### Features

- 15-ft. (4.57 m) USB 3.2 Gen 1 SuperSpeed cable
- SuperSpeed USB is 10 times faster than Hi-Speed USB, with transfer rates up to 5 Gbps.
- SuperSpeed USB is a Sync-N-Go technology that minimizes user wait-time.
- SuperSpeed USB will provide Optimized Power Efficiency...No device polling and lower active and idle power requirements.
- SuperSpeed USB is backwards compatible with USB 2.0. Devices interoperate with USB 2.0 platforms. Hosts support USB 2.0 legacy devices.

## Specifications

| OVERVIEW                  |              |
|---------------------------|--------------|
| UPC Code                  | 037332158079 |
| Technology                | USB 3.x      |
| Cable Type                | Passive      |
| PHYSICAL                  |              |
| Material of Construction  | PVC          |
| Cable Jacket Color        | Blue         |
| Cable Jacket Rating       | VW-1         |
| Cable Outer Diameter (OD) | 5.5MM        |
| Cable Length (ft.)        | 15           |

### Highlights

- 15ft SuperSpeed USB 3.2 Gen 1 A-B Cable
- 10 times faster than USB 2.0, with transfer rates up to 5 Gbps

### System Requirements

- Computers and Peripherals with USB 3.2 Gen 1 capabilities

### Package Includes

- 15-ft. (4.57 m) USB 3.2 Gen 1 SuperSpeed A-B Device cable

|                                      |                                     |
|--------------------------------------|-------------------------------------|
| Cable Length (m)                     | 4.57                                |
| Cable Length (in.)                   | 180                                 |
| Shipping Dimensions (hwd / in.)      | 7.00 x 9.00 x 0.50                  |
| Shipping Dimensions (hwd / cm)       | 17.78 x 22.86 x 1.27                |
| Shipping Weight (lbs.)               | 0.04                                |
| Shipping Weight (kg)                 | 0.02                                |
| <b>ENVIRONMENTAL</b>                 |                                     |
| Operating Temperature Range          | 14° to 140°F (-10° to 60°C)         |
| Storage Temperature Range            | -4° to 185°F (-20° to 85°C)         |
| Relative Humidity                    | 10% to 85%, Non-Condensing          |
| <b>CONNECTIONS</b>                   |                                     |
| Side A - Connector 1                 | USB A (MALE)                        |
| Side B - Connector 1                 | USB B (MALE)                        |
| Connector Plating                    | Nickel                              |
| Contact Plating                      | Gold                                |
| Connector Style                      | Straight                            |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                                     |
| USB Specification                    | USB 3.2 Gen 1 (up to 5 Gbps)        |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                                     |
| Product Compliance                   | RoHS; CE (Europe); REACH; FCC (USA) |
| <b>WARRANTY &amp; SUPPORT</b>        |                                     |
| Product Warranty Period (Worldwide)  | Lifetime limited warranty           |