



ASSEMBLY MATERIAL NO.	NO. OF CIRCUITS "XX"	"A"	"B"
	2		
	3		
387890242	4	63.5 (2.50)	55.6 (2.19)
	5		
387890243	6	85.9 (3.38)	77.7 (3.06)
	7		
387890244	8	108.0 (4.25)	100.0 (3.94)
	9		
387890245	10	130.3 (5.13)	122.2 (4.81)
	11		
387890246	12	152.4 (6.00)	144.5 (5.69)

- NOTES:
1. MATERIAL: SEE TABLE
 2. FINISHES: SEE TABLE
 3. PRODUCT SPECIFICATIONS: NOT REQUIRED
 4. PACKAGING: NOT REQUIRED
 5. MATE WITH: NONE

ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH
5	(XX)*2	SCREW	STEEL	ZN/CLEAR CHROMATE
4	XX	45° SINGLE TAB	BRASS	TIN
3	XX	SINGLE FAST TAB	BRASS	TIN
2	XX	TERMINAL	BRASS	NICKEL
1	1	INSULATOR	THERMOPLASTIC	BLACK

EC NO. ECNF 3406
 DRWN: WH (111)-03
 CHK: APPT:

DESCRIPTION

MAJOR

CRITICAL

SPEC

REV

GENERAL TOLERANCES UNLESS SPECIFIED	
mm	INCH
4 PLACES	±.0015
3 PLACES	±.038 ±.005
2 PLACES	±.13 ±.01
1 PLACE	±.3
ANGULAR: ±2°	

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

SCALE: [:]
 MM INCH

THIRD ANGLE PROJECTION

TITLE: SR BTS, CB, FT, ASY, 10A

MOLEX INCORPORATED

WATERL. NO. SEE CHART
 DRAWING NO. SD-38789-001
 SHEET NO. 1 OF 1

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

SIZE B

PROJECT NO.	1	REV