# 5164711-7 - ACTIVE

### MINI-MATCH TE Internal #: 5164711-7 PCB Mount Receptacle, Right Angle, Board-to-Board, 7 Position, 2.5 mm [.098 in] Centerline, Tin, Through Hole - Solder, Signal View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles



#### PCB Connector Assembly Type: PCB Mount Receptacle

PCB Mount Orientation: Right Angle

Connector System: Board-to-Board

Number of Positions: 7

Centerline (Pitch): 2.5 mm [.098 in]

### Features

### Product Type Features

PCB Connector Assembly Type	PCB Mount Receptacle
Connector System	Board-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

#### **Configuration Features**

Stackable	No
PCB Mount Orientation	Right Angle
Number of Positions	7
Electrical Characteristics	
Insulation Resistance	1 ΜΩ
Operating Voltage	354 VAC
Contact Features	
PCB Contact Termination Area Plating Material Thickness	3.04 – 5.08 μm[120 – 200 μin]
PCB Contact Termination Area Plating Material Thickness Contact Layout	3.04 – 5.08 μm[120 – 200 μin] Inline
Contact Layout	Inline
Contact Layout PCB Contact Termination Area Plating Material	Inline Tin
Contact Layout PCB Contact Termination Area Plating Material Contact Base Material	Inline Tin Brass
Contact Layout PCB Contact Termination Area Plating Material Contact Base Material Contact Mating Area Plating Material	Inline Tin Brass Tin

**C** For support call+1 800 522 6752

### 5164711-7

PCB Mount Receptacle, Right Angle, Board-to-Board, 7 Position, 2.5 mm [.098 in] Centerline, Tin, Through Hole - Solder, Signal



Contact Current Rating (Max)	7 A
Termination Features	
Rectangular Termination Post & Tail Thickness	.5 mm[.02 in]
Rectangular Termination Post & Tail Width	.79 mm[.031 in]
Termination Post & Tail Length	3.2 mm[.126 in]
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
PCB Mount Alignment Type	Post Polarization
PCB Mount Retention Type	Solder Tail
Mating Alignment	With
Mating Alignment Type	Polarizing Tab
PCB Mount Retention	With
PCB Mount Alignment	With
Connector Mounting Type	Board Mount
Housing Features	
Mating Entry Location	Side
Centerline (Pitch)	2.5 mm[.098 in]
Housing Material	Thermoplastic
Dimensions	
	1.27 in
Usage Conditions	
Operating Temperature Range	-40 – 85 °C[-40 – 185 °F]
Operation/Application	
Circuit Application	Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Quantity	2000
Packaging Type	Box

### Product Compliance

For compliance documentation, visit the product page on TE.com>

### 5164711-7

PCB Mount Receptacle, Right Angle, Board-to-Board, 7 Position, 2.5 mm [.098 in] Centerline, Tin, Through Hole - Solder, Signal



EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUL 2021 (219) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 240°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## **Compatible Parts**



### **Customers Also Bought**



### 5164711-7

PCB Mount Receptacle, Right Angle, Board-to-Board, 7 Position, 2.5 mm [.098 in] Centerline, Tin, Through Hole - Solder, Signal



### Documents

Product Drawings 07pos.MINI-MATCH FBTB, 2.5mm pitch

English

**CAD** Files

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_5164711-7\_A.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_5164711-7\_A.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_5164711-7\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Product Specifications

**Product Specification** 

Mini Match Connection System

English

**Product Specification** 

English

Instruction Sheets Instruction Sheet (non U.S.)

German