

Phytion™		Device Programmers and Development Tools for Microcontrollers				
Home	Products	E-Shop	Support	Contact	News	Site Map

Quick Links

- Help Desk
- Downloads
- All Programmers
- Device Search
- Tools Catalogs

Shopping Cart

Items: 0

Total: \$0.00


Your Account

Products

- Development Tools
 - ARM
 - 8051
 - Other
- Device programmers
 - All Models
 - Universal
 - In-System
 - Gang
 - Adapters
- Custom made tools
- OEM tools

AE-TS56-161-2

DIP40/ TSOP56 specialized adapter for FLASH memory.



Description:

DIP40/TSOP56 specialized adapter for FLASH memory. Device package dimensions: 14 x 20 mm, 0.5 mm pitch.

Supported Devices:

Click the device programmer model below to get an appropriate list of the devices supported by this programmer with this adapter:

- [ChipProg-48](#)
- [ChipProg-G4](#)
- [ChipProg-40](#)
- [ChipProg+](#)

[Adapter wiring diagram.](#)

Adapter Connection Table:

DIP-40	SSOP-56	74AHC573	C1, 150pF	C2, 0.1uF
1	21, 33			
2	44			
3	43			
4	38			
5	5			
6	45	4		
7		11	1	
8	56			
9	31			
10	47	7		
11	53			
12	55			
13	51	3		
14	39			
15	26			
16	16			
17	18			
18	17			
19	42			
20	4,15,20,37	1, 10	2	1
21	40			
22	19			
23	50	8		
24	35	9		
25	27			
26	24			
27	25			
28	49	6		
29	54			
30	52			

	31	29		
	32	41		
	33	46	5	
	34	32		
	35	48	2	
	36	22		
	37	30		
	38	3		
	39	36		
	40	1.28	20	2
		6	17	
		7	16	
		8	14	
		9	19	
		10	15	
		11	13	
		12	18	
		13	12	

Copyright © 2007-2010 Phyton, Inc.

Phone: 718-259-3191 • E-mails: info@phyton.com, sales@phyton.com, support@phyton.com