0.25 METER LENGTH



Connector A 132114RP SMA Plug Straight Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot Connector B 122454 TNC Jack Right Angle Bulkhead - Rear Mount Brass Nickel + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

	Connector A			Cable		Connector B		
Part #: Descript Type: Gender: Body Ty Contact Polarity: Impedar Mountin Body Ma Body Fin IP Rating Contact Contact Max. Fre Booting	SMA Plug Plug Straight Type: Crimp : Reverse force: 50 Ohm g: Cable aterial: Brass nish: Gold g: None Material: Beryllium Copper Finish: Gold eq.: 12.4 GHz		Part #: Description: Dielectric: Shielding: Diameter: Impedance: Sheathing: Testing: Length:	RG-174 RG-174 - PE 0.1 PE Braid 0.1 50 Ohm None Continuity Hi-Pot 0.25 Meter	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting: Clocking:	122454 TNC R/A BHD JK R 500 TNC Jack Right Angle Solder Standard 50 Ohm Bulkhead - Rear Mo Brass Nickel None Phosphor Bronze Gold 11 GHz TNC Jack Right Ang 0°		
Amphenol		THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.				UNLESS SPECIFIED TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES		