

# CA-00000002S00 - Panel mounting base



1620541

<https://www.phoenixcontact.com/us/products/1620541>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector, front mounting without contact insert, straight, SPEEDCON locking, M23, flat gasket, 4x Ø 3.2, shielded: yes, flange dimensions: 25 mm x 25 mm

## Commercial data

Item number	1620541
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AB33
Product key	ABRAEP
GTIN	4046356828857
Weight per piece (including packing)	22 g
Weight per piece (excluding packing)	19.92 g
Customs tariff number	85366990
Country of origin	DE

# CA-00000002S00 - Panel mounting base



1620541

<https://www.phoenixcontact.com/us/products/1620541>

## Technical data

### Product properties

Product type	Panel mounting base
Application	Signal
Series	CA
Shielded	yes
Thread type	M23

### Dimensions

#### Housing

Flange dimensions	25 mm x 25 mm
-------------------	---------------

### Material specifications

Housing material	GD-Zn
------------------	-------

### Connector

Type	straight
------	----------

### Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP67
Altitude	2000 m

### Mounting

Mounting	4x Ø 3.2
----------	----------

# CA-00000002S00 - Panel mounting base



1620541

<https://www.phoenixcontact.com/us/products/1620541>

## Classifications

### ECLASS

ECLASS-11.0	27440312
ECLASS-13.0	27440312
ECLASS-12.0	27440312

### ETIM

ETIM 8.0	EC002641
----------	----------

### UNSPSC

UNSPSC 21.0	31261500
-------------	----------

# CA-00000002S00 - Panel mounting base



1620541

<https://www.phoenixcontact.com/us/products/1620541>

## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

# CA-00000002S00 - Panel mounting base



1620541

<https://www.phoenixcontact.com/us/products/1620541>

## Accessories

### CA-Z0120 - Color-coding

1620704

<https://www.phoenixcontact.com/us/products/1620704>

Color-coding, color: green



---

### CA-Z0121 - Color-coding

1620705

<https://www.phoenixcontact.com/us/products/1620705>

Color-coding, color: orange



# CA-00000002S00 - Panel mounting base

1620541

<https://www.phoenixcontact.com/us/products/1620541>



## CA-Z0122 - Color-coding

1620706

<https://www.phoenixcontact.com/us/products/1620706>

Color-coding, color: black



---

## SF-Z0019 - Protective cap

1607449

<https://www.phoenixcontact.com/us/products/1607449>

Plastic protection cap, with eye, IP40 for connectors with M23 external thread, RF, SF series



# CA-00000002S00 - Panel mounting base



1620541

<https://www.phoenixcontact.com/us/products/1620541>

## RC-Z2059 - Protective cap

1604225

<https://www.phoenixcontact.com/us/products/1604225>

Plastic protection cap for connectors with M23 external thread



---

## RC-Z2469 - Protective cap

1611797

<https://www.phoenixcontact.com/us/products/1611797>

Plastic protection cap, antistatic, for RF, SF, CA, RC series connectors, with M23 external thread



# CA-00000002S00 - Panel mounting base



1620541

<https://www.phoenixcontact.com/us/products/1620541>

## RC-Z2104 - Metal protective cap

1604260

<https://www.phoenixcontact.com/us/products/1604260>



Metal protective cap, M23, degree of protection: IP67, series: RC, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1241739

## RC-Z2068 - Metal protective cap

1604236

<https://www.phoenixcontact.com/us/products/1604236>



Metal protective cap, M23, degree of protection: IP67, series: RC, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1241735

Phoenix Contact 2023 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)