



AUX. VIEW
SCALE 1:1
9 CIRCUIT SHOWN

NO. OF CIRCUITS "XX"	DIM. "B"	MATERIAL NO.
06	5.08 (1.200)	39880-0806
09	10.16 (1.400)	39880-0809
12	15.24 (1.600)	39880-0812
15	20.32 (1.800)	39880-0815
18	25.40 (1.000)	39880-0818
21	30.48 (1.200)	39880-0821
24	35.56 (1.400)	39880-0824
27	40.64 (1.600)	39880-0827
30	45.72 (1.800)	39880-0830
33	50.80 (2.000)	39880-0833
36	55.88 (2.200)	39880-0836
39	60.96 (2.400)	39880-0839
42	66.04 (2.600)	39880-0842
45	71.12 (2.800)	39880-0845
48	76.20 (3.000)	39880-0848
51	81.28 (3.200)	39880-0851
54	86.36 (3.400)	39880-0854
57	91.44 (3.600)	39880-0857
60	96.52 (3.800)	39880-0860
63	101.60 (4.000)	39880-0863
66	106.68 (4.200)	39880-0866
69	111.76 (4.400)	39880-0869
72	116.84 (4.600)	39880-0872

- NOTES:
1. MATERIAL: SEE TABLE
 2. FINISHES: SEE TABLE
 3. PRODUCT SPECIFICATION: NOT REQUIRED
 4. PACKAGING: NOT REQUIRED
 5. MATES WITH: NONE
 6. "XX" REFERS TO THE QUANTITY OF CIRCUITS.

PTH PATTERN

ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH
4	XX	SCREW, M3	BRONZE	NICKEL PLATE
3	XX	RISING CAGE CLAMP	BRASS	NICKEL PLATE
2	XX	TERMINAL	COPPER ALLOY	TIN PLATE
1	1	INSULATOR, THREE LEVEL	POLYAMIDE	BLACK

EC NO. DRAWN: CH'KT APPR: A	DESCRIPTION MAJOR CRITICAL SPC S	GENERAL TOLERANCES: (UNLESS SPECIFIED)		SCALE 2:1	DESIGN UNITS <input type="checkbox"/> mm <input checked="" type="checkbox"/> INCH	THIRD ANGLE PROJECTION	PROJECT NO. - DIMENSIONS: <input checked="" type="checkbox"/> mm <input type="checkbox"/> INCH <input type="checkbox"/> mm <input type="checkbox"/> ONLY	SHT REV
		4 PLACES ±.0015 3 PLACES ±.038 ±.005 2 PLACES ±.13 ±.01 1 PLACE ±.3	ANGULAR: ±2°	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	DRAWN BY & DATE C. YORK 11-29-04	CHECKED BY & DATE	APPROVED BY & DATE	TITLE: 5.08mm (.200") LOW PROFILE, THREE LEVEL TERM. BLOCK
CAD FILENAME 8831XX				THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.		MATERIAL NO. SEE CHART	DRAWING NO. SD-39880-010	SHEET NO. 1 OF 1
							MOLEX INCORPORATED	SIZE B