

## Universal Reversible USB 2.0 Adapter (Reversible A to Up Angle A M/F)

MODEL NUMBER: UR024-000-UP



Turn your standard USB cable into a Universal Cable

### Description

The UR024-000-UP USB adapter (M/F) features a universal/reversible male end which allows the adapter to be plugged in any direction on a computer's USB port. Add this adapter to a standard USB cable, and convert it to a universal pluggable cable. The up-angle USB-A connector is ideal in situations where space is at a premium. USB 2.0 rated for 480 Mbps transfer rates. Fully molded with gold-plated contacts for a lifetime of use.

### Features

- USB 2.0 Male-to Female adapter, with Universal / Reversible Male connector
- Male end can be plugged in any direction
- Up-Angle A connector ideal in situations where space is at a premium
- USB2.0 Hi-Speed rated

## Specifications

| OVERVIEW           |                      |
|--------------------|----------------------|
| UPC Code           | 037332182920         |
| Technology         | USB 2.0 (High Speed) |
| Cable Type         | Passive              |
| PHYSICAL           |                      |
| Cable Jacket Color | Black                |
| Cable Length (ft.) | 0                    |
| Cable Length (m)   | 0.00                 |

### Highlights

- Universal / Reversible A-Male plugs in any direction
- Turns a standard USB cable into a Universal Cable
- Up-Angle A connector ideal in situations where space is at a premium
- USB2.0 Rated

### Package Includes

- Universal Reversible USB 2.0 A-Male to Up-Angle A-Female Adapter

|                                      |                              |
|--------------------------------------|------------------------------|
| Shipping Dimensions (hwd / in.)      | 6.00 x 4.50 x 0.50           |
| Shipping Dimensions (hwd / cm)       | 15.24 x 11.43 x 1.27         |
| Shipping Weight (lbs.)               | 0.01                         |
| Unit Dimensions (hwd / in.)          | 6.000 x 4.500 x 0.500        |
| <b>ENVIRONMENTAL</b>                 |                              |
| Operating Temperature Range          | 14° to 122°F (-10° to 50°C)  |
| Storage Temperature Range            | 5° to 140°F (-15° to 60°C)   |
| Operating Humidity Range             | 0% to 90% RH, Non-Condensing |
| Storage Humidity Range               | 0% to 90% RH, Non-Condensing |
| <b>CONNECTIONS</b>                   |                              |
| Side A - Connector 1                 | REVERSIBLE USB A (MALE)      |
| Side B - Connector 1                 | USB A (FEMALE)               |
| Connector Style                      | Angled                       |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                              |
| USB Specification                    | USB 2.0 (up to 480 Mbps)     |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                              |
| Product Compliance                   | RoHS                         |
| <b>WARRANTY &amp; SUPPORT</b>        |                              |
| Product Warranty Period (Worldwide)  | Lifetime limited warranty    |