



Material
 Item @ Clamp : Brass(CuZn) Ni plated
 Item Ⓛ Terminal screw: Steel Zinc plating "I" slot type
 Item ⓐ Female contact : PhBz(CuZn)Tin plated
 Item Ⓚ Terminal housing: Thermoplastic (UL94V-0)
 Green(RAL6018/T)

Electrical cULus
 Voltage rating: 300V
 Current rating: 10A
 Wire range:
 Solid wire(AWG): 16-28
 Stranded wire(AWG): 16-28
 Torque(Lb-In): 1.7
 Screw: M2
 Wire strip length: 5-6mm
 Withstanding Voltage: 1.6KV
 Ⓞ Operating temperature: -40°C to +115°C
 Safety approval: cULus

DIMENSION

A	Nx3.5
B	(N-1)x3.5

N=Number of poles

Poles	Tolerance	DIM A	DIM B
4p-6p		±0.20	±0.15
7p-12p		±0.25	±0.20
13p-24p		±0.30	±0.25

RoHS compliant
 Unit: mm

 File No.: E349947

Scale	Free TOLERANCE	Free
X.	±0.50	
X.X	±0.30	
X.XX	±0.10	
DIM	TOL	
X.°	±1°	
Angle	TOL	

Id.	Modification	Date	Name
①	Drawn	30.11.2006	Hellwig
②	Update	20.04.2010	Alex
③	Update to new drawing and add UL	25.03.2016	Amy

Customer-No.	Name	Date	Approved
	Hellwig	30.11.2006	Drawn
	Amy	25.03.2016	Approved

ASSMANN WSW-No. **A-TB350-THXX**

ASSMANN Drawing-No. **ASS 1150 CO**



Replace Sheet

1	2	3	4	5	6	7	A
1	2	3	4	5	6	7	B
1	2	3	4	5	6	7	C
1	2	3	4	5	6	7	D
1	2	3	4	5	6	7	E
1	2	3	4	5	6	7	F
1	2	3	4	5	6	7	G
1	2	3	4	5	6	7	H