



- NOTES:**
1. METALSHELLS: STEEL; min. 315 $\mu$ m TIN over 40-80 $\mu$ m NICKEL
  2. INSULATORS: PA 6.6 UL 94 V-0, BLACK
  3. FRAME: STEEL; NICKEL PLATED
  4. FLOAT MOUNTS: COPPER ALLOY; NICKEL PLATED
  5. RIVETED INSERTS: COPPER ALLOY; min. 200 $\mu$ m TIN over 80 $\mu$ m NICKEL
  6. COLLARS: COPPER ALLOY; min. 200 $\mu$ m TIN over 80 $\mu$ m NICKEL
  7. CONNECTOR IS PART MARKED: 16-507360 CONEC ABC

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND	Customer Specific Product with special float frame		tolerance		dim. in mm	scale: 2:1 (5:1)			
						material: SEE NOTES			
			date	name		title: <b>D- SUB HD FEMALE</b> 78pos. CRIMP STYLE with frame, float for blind mating system			
			drawn	21.03.13	Henneboel				
			appd.	22.03.13	Fischer				
			norm		d-old		dwg no:		
							16K1A3208		
						part no: 16-507360			
						DIN-A3 sh: 1			

