



CORE DIMENSIONS					
UNCOATED CORE			33T0255-100		
	MM	INCHES		MM	INCHES
OD	6.48	(.255)	±	.15	(.006)
ID	2.49	(.098)	±	.13	(.005)
TH	3.99	(.157)	±	.13	(.005)
PARYLENE			33T0255-10P		
OD	6.50	(.256)	±	.15	(.006)
ID	2.46	(.097)	±	.13	(.005)
TH	4.01	(.158)	±	.13	(.005)

INITIAL PERMEABILITY 2700
WEIGHT / K 1.20 LBS

ELECTRICAL SPECIFICATION								
	MIN (μ H)	MIN TOL.	NOM (μ H)	MAX (μ H)	MAX TOL.	FREQ. (kHz)	VOLT. (mV)	TURNS
L	1.647	(-20%)	2.059	2.471	(+20%)	100	≤ 1.64	1
Q	62	-	-	-	-	100	≤ 1.64	1

COATING SPECIFICATIONS			
TYPE	coating thickness (mils.)	Min. DLB VAC	TEST FORCE (LB)
PARYLENE	0.5	1000	.44

NOTES:



Rev	Description	Date	INT
A	Original Draft	6/2/1999	TPM
B	RE-ACTIVATE PRINT	10/19/2005	JRK
C	REVISED TEMPLATE	4/4/2006	WMM

Date: 4/4/06	DWG # 33T0255-10P-C	Rev:
Drawn By: WMM	Title # 33T0255-10P	C

Steward This document contains information which is proprietary to Steward. No production or publication of this document in whole or in part shall be made without written authorization from Steward.