



NOTES:
 1. MATERIAL: COPPER
 PLATING: ELECTRO-TIN
 2. INSULATION: MOLDED NYLON (YELLOW)
 3. ASSEMBLY IS ROHS COMPLIANT.

MWID=MAXIMUM WIRE INSULATION DIAMETER

STUD SIZE	"S" ±.005
02	.094
04	.119
06	.146
08	.173
10	.198
14	.265
56	.328
38	.390
76	.453
12	.515
209	.209
413	.413

PART NUMBER	"W" ±.010	"C" MIN	"L" MAX	AVAILABLE STUD SIZES	THICKNESS REF
F-966-	.668	.520	1.95	209, 413, 10, 14, 56, 38, 76, 12	.067
F-967-	.475	.520	1.85	10, 14, 56	.067
F-969-	.885	.989	2.53	10, 14, 56, 38, 76, 12, 58	.070
F-970-	1.260	.989	2.72	14, 56, 38, 76, 12, 58, 34	.070

REDWIN W/REDUCED THICKNESS EC NO: ETC2007-0019 DRAWN: EHILE 2007/08/22 CHK'D: JMACNEIL 2007/09/11 APPR: JMACNEIL 2007/09/19	DESCRIPTION A	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE INCH ONLY		SCALE ---	DESIGN UNITS INCH	THIRD ANGLE PROJECTION		
				mm	INCH	DRAWN BY RCM	DATE 1994/03/16	TITLE RING TONGUE TERMINAL, FUNNEL ENTRY NYLAKRIMP, 4 AWG			
			4 PLACES	± ---	± ---	CHECKED BY ---	DATE ---				
			3 PLACES	± ---	± ---	APPROVED BY ---	DATE ---				
2 PLACES	± ---	± ---	ANGULAR ± ---°		MATERIAL NO. SEE CHART		DOCUMENT NO. SD-19067-018		SHEET NO. 1 OF 1		
1 PLACE	± ---	± ---	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SIZE A		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				