

GENERAL SPECIFICATIONS:

VOLTAGE: 300 V 80°C TEMPERATURE:

CABLE TYPE / SIZE: UL1185, 24 AWG, 1C+SHIELD

CABLE JACKET COLOR: **BLACK**

OVERALL LENGTH (L): 680 +10,-0 mm

END 'A' TERMINATION: SPRING LO END 'B' TERMINATION: SPRING LO

APPROVALS CABLE: UL, CSA OR CUL APPROVALS CONNECTOR: UL, CSA OR CUL

DADED, LOCKING NOTCH,	FEMALE BARREL 5.5 x 2.1 x 11 mm
DADED, LOCKING NOTCH,	FEMALE BARREL 5.5 x 2.5 x 11 mm
OR CUI	

DASH

PACKING:

BULK PACKED, BUNDLES OF 25.

MAXIMUM SHIPPING CARTON WEIGHT IS 30 kgs.

End A	Cable	End B
Center	Black	Center
Outside	Shield	Outside

NOTES:

Contents of this document

prior notice

are subject to change without

1. CORD MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBER(S).





installation instruction.

Globtek Inc. will not be liable for the

safety and performance of these power

product if unauthorized access and repair

ble UL,CSA or EN Standards for proper

occurs. End user should consult the applica-



Globtek product are not authorized for use as mission critical components in life support, hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of Globtek Inc.

	DASH NO.]	PART NO	REV.		DESCRIPTION	NOTES	
TABULATION BLOCK								
				TOLD DECIM .xx +/xxx +/-	· 0.1 +/- 1° · .005	GlobTek, Inc. www.globtek.com 186 Veterans Dr. Nor Tel. 201-784-1000 F		
	INIT.BY: 1	MS	DATE: 11/18/10	MILLIME .xx +/- (.xxx +/	0.3 +/- 1°	DWG TITLE: OUTPUT CABLE ASSEMBLY		
	DRAWN:	NF	DATE: 11/18/10	FSCN N G, T	No.: SIZE A		REV. B	
	APRVD:	НМ	DATE: 11/18/10	SCALE: NONE		PART NO: CSP11850M68LSP(R)	SHEET 1/1	