



PANDUIT PART NO	BUNDLE DIAM		A in (mm)	B in (mm)	C in (mm)	D in (mm)	E in (mm)	F in (mm)	LOOP TENSILE lbs (N)	CROSS SECTION	WEIGHT lbs (g) / 100 pcs	TIP STYLES
	MIN in (mm)	MAX in (mm)										
S12-50	.12 (3.0)	2.99 (76)	.051 (1.3)	.19 (4.8)	.307 (7.8)	.23 (5.9)	.331 (8.4)	11.81 (300)	50 (222)	STANDARD	0.461 (209.1)	CURVED
S15-50	.12 (3.0)	4.02 (102)	.051 (1.3)	.19 (4.8)	.299 (7.6)	.23 (5.9)	.331 (8.4)	14.57 (370)	50 (222)	STANDARD	0.521 (236.3)	CURVED
S17-50	.12 (3.0)	4.33 (110)	.051 (1.3)	.19 (4.8)	.307 (7.8)	.23 (5.9)	.331 (8.4)	16.90 (430)	50 (222)	STANDARD	0.668 (303)	STRAIGHT
S21-50	.12 (3.0)	5.51 (140)	.055 (1.4)	.19 (4.8)	.307 (7.8)	.23 (5.9)	.326 (8.3)	20.87 (530)	50 (222)	STANDARD	.804 (364.7)	STRAIGHT

NOTE:
SEE WWW.PANDUIT.COM FOR PART NUMBER SUFFIX DESIGNATION FOR PACKAGE SIZE, PART MATERIAL,
PART COLOR AND ANY THIRD PARTY RECOGNITION OR COMPLIANCE.

						<p>TITLE</p> <p style="text-align: center;">STRONGHOLD STANDARD TIES</p> <p style="text-align: center;">CUSTOMER DRAWING</p>						
						<p>ITEM REVISION NAME</p> <p style="text-align: center;">00092FBK/00</p>						
						<p>DATASET FILE NAME</p> <p style="text-align: center;">00092FBK_DC/00</p>						
						<p>UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm]</p> <p>.x ± .1 [2.54] .xxx ± .020 [.51]</p> <p>.xx ± .02 [.51] ANGLES ± 5°</p>						
						<p>MATERIAL:</p> <p style="text-align: center;">NYLON 6.6</p>						
						<p>DRAWING NUMBER:</p> <p style="text-align: center;">00092FBK_DC</p>						
00	3/15/17	ACC	JSWA	JADE	DRAWING RELEASED	012502						
REV	DATE	BY	CHK	APR	DESCRIPTION	ECN	DRAWN BY	DATE	CHK	SCALE	SHT 1 OF 1	
							ACC	2-22-17	JSWA	N/A	A	

D10100DA/20