K21F1C-P08LFG0-350S

series_f, type_k2



General information

| Part number | K21F1C-P08LFG0-350S | |
|-------------------|---------------------|--------|
| Termination | solder | |
| Size | 1 | |
| Locking principle | break , push | C FUIL |
| Coding | 1_halfshell | |
| Cable Diameter | cable_mini_35 | |
| Cable outlet | bend_relief | |
| | | |



Contact insert description

| Number of contacts | 8 |
|----------------------|---------|
| Contact type | sockets |
| Contact diameter | 07mm |
| Insulator material | peek |
| Wire cross section | 22_awg |
| Termination | solder |
| Termination diameter | 085mm |

reverse_gender_on_request

Technical information

| Max. creepage and air clearance distance | 04_mm | 07_mm |
|--|----------|---------------|
| Nominal current single contact | 075_a | iec_60512_5_2 |
| Nominal current insert | 4,875 A | vde_0298_4 |
| Test voltage | 09_kv_ac | sae_13441 |

safety_text

Mechanical and environmental data

| Degree of protection* | ip50 | |
|-----------------------|----------|--|
| Operating temperature | 40_120_c | |
| Mating cycles | 5000 | |
| mated unmated | | |

Material and surface treatments

Housing

m_chrome

Contact

cu_alloy_gold

safety_text_2 ul_text illustrative_text