


THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.


NOTES:

1. SEE SHEETS 2 & 3 FOR PRODUCT DESCRIPTIONS AND TECHNICAL SPECIFICATIONS.
2. SEE CURRENT CATALOG FOR PATCH CORD LENGTHS AND PACKAGE QUANTITY.
3. FOR LENGTHS OTHER THAN THOSE LISTED IN CATALOG, CONTACT YOUR PANDUIT SALES PERSON.
4. TESTED TO EIA/TIA 568-B.3.
5. PATCH CORD ROUTING CONFIGURATION A TO B.
6. ALL MATERIALS AND COMPONENTS USED MEET THE MATERIAL RESTRICTIONS OF RoHS, (EUROPEAN DIRECTIVE 2002/95/EC ON THE RESTRICTION OF HAZARDOUS SUBSTANCES) AS PROPOSED BY THE RoHS TECHNICAL ADAPTATION COMMITTEE.



FEMALE MTP CONNECTOR
SHOWN WITHOUT DUSTCAP

FEMALE MTP CONNECTOR
SHOWN WITH DUSTCAP

											FIBER OPTIC PATCH CORD MTP TO MTP CONFIGURATION CUSTOMER DRAWING					
												 TINLEY PARK, ILL 60477				
											 THIRD ANGLE PROJECTION	ALL DIMENSIONS ARE GIVEN IN INCHES UNLESS OTHERWISE SPECIFIED.		DRAWING FILENAME M02779BG_DC/01A		
										DIMENSIONAL TOLERANCES ARE: (.X) ±.03 (.XXX) ±.010 (.3) ±.010 (.XX) ±.03 (.0.8) ANGLES		SCALE NONE				
										DRAWN BY MC		REVIEW DRAWING NUMBERS		PART NO. SEE SHEETS 2 & 3		
												DATE 05-03-07		DRAWING NO. 02779-15 SHEET 1 of 3		SIZE A
01	09-09-09	EFK		RELEASED TO PRODUCTION		02779-15										
REV	DATE	BY	CHK	DESCRIPTION		ECN - R		CUST	SUP	OTH	CHK'D	RAF				

