

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	K2	REVISED PER ECR-15-013036	03SEP2015	NK	DC

PACKAGING DETAILS:
 QUANTITY PER REEL: 8000 PCS(END FEED).
 SPLICES FREE

Left-sided product

Right-sided product

Rango de hilo de 0,5 a 1,5 mm²
 Wire range from 0.5 to 1.5 mm²
 Diametro de aislante max 3,0 mm
 Max. Insulation Diameter 3.0 mm

336075-7 (REELED WITH PAPER INTERLEAVE)	Latón Brass	Preestañado Pre-Tin
336075-6	CuNiSi	Preestañado Pre-Tin
336075-5	Acero Steel	Preniquelado Pre-Ni
336075-3	Latón Brass	Preestañado Pre-Tin
336075-1	Latón Brass	-
Guion Dash	Material	Acabado Finish

DIRECTION OFF TOP OF REEL

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN J. Saló 22 Dec 04

CHK L. L. 22 Dec 04

APVD -

PRODUCT SPEC
108-22128 Brass
108-22150 Pre-Ni Steel

APPLICATION SPEC

114-22017

WEIGHT -

Customer Drawing

DIMENSIONS:
mm

MATERIAL
Table

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	±0.5
1 PLC	±0.5
2 PLC	±
3 PLC	±
4 PLC	±
ANGLES	±

FINISH
Table

NAME
E-SPRING CONTACT 6,35 Receptaculo
6.35 Receptacle E-SPRING CONTACT

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	C=336075	-

SCALE	SHEET	OF	REV
4:1	1	1	K2

1470-19 (3/13)