



注記
NOTES

1. 各部の反りは0.5最大。
WARPING : 0.5 MAX.
2. サークットNO.はNO."1"のみ表示。
CIRCUIT NO. : 1 ONLY.
3. PDR NO. 39-01-4**8

17.5	12.5	39-01-4038	5199-033	3
12.5	7.5	39-01-4028	5199-023	2
B	A	EDP. NO.	MATERIAL NO.	種数 NO. OF CKTS.
			MODEL NO.	5199-N3

REVISED EC NO. J2008-4275 DRWN:NAKURAA 2008/07/01 CHKD:T. HARUYAMA 2008/07/01 APPR:NUKITA 2008/11/19 REV A	DESCRIPTION GENERAL TOLERANCES (UNLESS SPECIFIED) 10 UNDER ±0.2 10 OVER 30 UNDER ±0.25 30 OVER ±0.3 ANGULAR ±3 ° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION	
		MM ONLY	4:1	METRIC		
		TITLE				SHEET NO.
		SPOX 5/7.5 REC HSG				1 OF 1
DRAWN BY		DATE	TITLE			
H. HIRAMOTO		'91/8/20	SPOX 5/7.5 REC HSG			
CHECKED BY		DATE	MATERIAL NO.			
M. FUKUSHIMA		'91/8/22	5199-N3			
APPROVED BY		DATE	MATERIAL NO.			
M. ENOMOTO		'91/8/22	5199-N3			
MATERIAL NO.		DOCUMENT NO.	SHEET NO.			
SEE TABLE		SD-5199-002	1 OF 1			
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION						

材料
MATERIAL
ナイロン66, UL94V-0
NYLON66, UL94V-0