



SIMATIC S7-1200F, CPU 1214 FC, compact CPU, DC/DC/relay, onboard I/O: 14 DI 24 V DC; 10 DO relay 2 A; 2 AI 0-10 V DC, Power supply: DC 20.4-28.8V DC, Program/data memory 125 KB

General information	
Product type designation	CPU 1214FC DC/DC/Relay
Firmware version	V4.5
Engineering with	
<ul style="list-style-type: none"> <li>Programming package</li> </ul>	STEP 7 V17 or higher
Supply voltage	
Rated value (DC)	
<ul style="list-style-type: none"> <li>24 V DC</li> </ul>	Yes
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Load voltage L+	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> <li>permissible range, lower limit (DC)</li> <li>permissible range, upper limit (DC)</li> </ul>	24 V 20.4 V 28.8 V
Input current	
Current consumption (rated value)	500 mA; CPU only
Current consumption, max.	1 500 mA; CPU with all expansion modules
Inrush current, max.	12 A; at 28.8 V
I <sup>2</sup> t	0.8 A <sup>2</sup> ·s
Output current	
for backplane bus (5 V DC), max.	1 600 mA; Max. 5 V DC for SM and CM
Encoder supply	
24 V encoder supply	
<ul style="list-style-type: none"> <li>24 V</li> </ul>	L+ minus 4 V DC min.
Power loss	
Power loss, typ.	12 W
Memory	
Work memory	
<ul style="list-style-type: none"> <li>integrated</li> <li>expandable</li> </ul>	125 kbyte No
Load memory	
<ul style="list-style-type: none"> <li>integrated</li> <li>Plug-in (SIMATIC Memory Card), max.</li> </ul>	4 Mbyte with SIMATIC memory card
Backup	
<ul style="list-style-type: none"> <li>present</li> <li>maintenance-free</li> <li>without battery</li> </ul>	Yes Yes Yes
CPU processing times	
for bit operations, typ.	0.08 μs: / instruction

for word operations, typ.	1.7 µs; / instruction
for floating point arithmetic, typ.	2.3 µs; / instruction
<b>CPU-blocks</b>	
Number of blocks (total)	DBs, FCs, FBs, counters and timers. The maximum number of addressable blocks ranges from 1 to 65535. There is no restriction, the entire working memory can be used
<b>OB</b>	
• Number, max.	Limited only by RAM for code
<b>Data areas and their retentivity</b>	
Retentive data area (incl. timers, counters, flags), max.	14 kbyte
<b>Flag</b>	
• Size, max.	8 kbyte; Size of bit memory address area
<b>Local data</b>	
• per priority class, max.	16 kbyte; Priority class 1 (program cycle): 16 KB, priority class 2 to 26: 6 KB
<b>Address area</b>	
<b>Process image</b>	
• Inputs, adjustable	1 kbyte
• Outputs, adjustable	1 kbyte
<b>Hardware configuration</b>	
Number of modules per system, max.	3 comm. modules, 1 signal board, 8 signal modules
<b>Time of day</b>	
<b>Clock</b>	
• Hardware clock (real-time)	Yes
• Backup time	480 h; Typical
• Deviation per day, max.	±60 s/month at 25 °C
<b>Digital inputs</b>	
Number of digital inputs	14; Integrated
• of which inputs usable for technological functions	6; HSC (High Speed Counting)
Source/sink input	Yes
<b>Number of simultaneously controllable inputs</b>	
all mounting positions	
— up to 40 °C, max.	14
<b>Input voltage</b>	
• Rated value (DC)	24 V
• for signal "0"	5 V DC at 1 mA
• for signal "1"	15 V DC at 2.5 mA
<b>Input delay (for rated value of input voltage)</b>	
for standard inputs	
— parameterizable	0.2 ms, 0.4 ms, 0.8 ms, 1.6 ms, 3.2 ms, 6.4 ms and 12.8 ms, selectable in groups of four
— at "0" to "1", min.	0.2 ms
— at "0" to "1", max.	12.8 ms
for interrupt inputs	
— parameterizable	Yes
for technological functions	
— parameterizable	Single phase: 3 @ 100 kHz & 3 @ 30 kHz, differential: 3 @ 80 kHz & 3 @ 30 kHz
<b>Cable length</b>	
• shielded, max.	500 m; 50 m for technological functions
• unshielded, max.	300 m; for technological functions: No
<b>Digital outputs</b>	
Number of digital outputs	10; Relays
<b>Switching capacity of the outputs</b>	
• with resistive load, max.	2 A
• on lamp load, max.	30 W with DC, 200 W with AC
<b>Output delay with resistive load</b>	
• "0" to "1", max.	10 ms; max.
• "1" to "0", max.	10 ms; max.
<b>Relay outputs</b>	

<ul style="list-style-type: none"> <li>• Number of relay outputs</li> <li>• Number of operating cycles, max.</li> </ul>	10 mechanically 10 million, at rated load voltage 100 000
<b>Cable length</b>	
<ul style="list-style-type: none"> <li>• shielded, max.</li> <li>• unshielded, max.</li> </ul>	500 m 150 m
<b>Analog inputs</b>	
Number of analog inputs	2
<b>Input ranges</b>	
<ul style="list-style-type: none"> <li>• Voltage</li> </ul>	Yes
<b>Input ranges (rated values), voltages</b>	
<ul style="list-style-type: none"> <li>• 0 to +10 V — Input resistance (0 to 10 V)</li> </ul>	Yes ≥100k ohms
<b>Cable length</b>	
<ul style="list-style-type: none"> <li>• shielded, max.</li> </ul>	100 m; twisted and shielded
<b>Analog outputs</b>	
Number of analog outputs	0
<b>Analog value generation for the inputs</b>	
<b>Integration and conversion time/resolution per channel</b>	
<ul style="list-style-type: none"> <li>• Resolution with overrange (bit including sign), max.</li> <li>• Integration time, parameterizable</li> <li>• Conversion time (per channel)</li> </ul>	10 bit Yes 625 μs
<b>Encoder</b>	
<b>Connectable encoders</b>	
<ul style="list-style-type: none"> <li>• 2-wire sensor</li> </ul>	Yes
<b>1. Interface</b>	
Interface type	PROFINET
Isolated	Yes
automatic detection of transmission rate	Yes
Autonegotiation	Yes
Autocrossing	Yes
<b>Interface types</b>	
<ul style="list-style-type: none"> <li>• RJ 45 (Ethernet)</li> <li>• Number of ports</li> <li>• integrated switch</li> </ul>	Yes 1 No
<b>Protocols</b>	
<ul style="list-style-type: none"> <li>• PROFINET IO Controller</li> <li>• PROFINET IO Device</li> <li>• SIMATIC communication</li> <li>• Open IE communication</li> <li>• Web server</li> <li>• Media redundancy</li> </ul>	Yes Yes Yes Yes; Optionally also encrypted Yes No
<b>PROFINET IO Controller</b>	
<ul style="list-style-type: none"> <li>• Transmission rate, max.</li> </ul>	100 Mbit/s
<b>Services</b>	
<ul style="list-style-type: none"> <li>— PG/OP communication</li> <li>— Isochronous mode</li> <li>— IRT</li> <li>— PROFIenergy</li> <li>— Prioritized startup</li> <li>— Number of IO devices with prioritized startup, max.</li> <li>— Number of connectable IO Devices, max.</li> <li>— Number of connectable IO Devices for RT, max.</li> <li>— of which in line, max.</li> <li>— Activation/deactivation of IO Devices</li> <li>— Number of IO Devices that can be simultaneously activated/deactivated, max.</li> <li>— Updating time</li> </ul>	Yes; encryption with TLS V1.3 pre-selected No No No Yes 16 16 16 16 Yes 8 The minimum value of the update time also depends on the communication component set for PROFINET IO, on the number of IO devices and the quantity of configured user data.

PROFINET IO Device	
<b>Services</b>	
— PG/OP communication	Yes; encryption with TLS V1.3 pre-selected
— Isochronous mode	No
— IRT	No
— PROFIenergy	Yes
— Shared device	Yes
— Number of IO Controllers with shared device, max.	2
<b>Protocols</b>	
Supports protocol for PROFINET IO	Yes
PROFIsafe	Yes
PROFIBUS	Yes; CM 1243-5 (master) or CM 1242-5 (slave) required
OPC UA	Yes; OPC UA Server
AS-Interface	Yes; CM 1243-2 required
<b>Protocols (Ethernet)</b>	
• TCP/IP	Yes
• DHCP	No
• SNMP	Yes
• DCP	Yes
• LLDP	Yes
<b>Open IE communication</b>	
• TCP/IP	Yes
— Data length, max.	8 kbyte
• ISO-on-TCP (RFC1006)	Yes
— Data length, max.	8 kbyte
• UDP	Yes
— Data length, max.	1 472 byte
<b>Web server</b>	
• supported	Yes
• User-defined websites	Yes
<b>OPC UA</b>	
• Runtime license required	Yes; "Basic" license required
• OPC UA Server	Yes; data access (read, write, subscribe), method call, runtime license required
— Application authentication	Available security policies: None, Basic128Rsa15, Basic256Rsa15, Basic256Sha256
— User authentication	"anonymous" or by user name & password
— Number of sessions, max.	10
— Number of subscriptions per session, max.	50
— Sampling interval, min.	100 ms
— Publishing interval, min.	200 ms
— Number of server methods, max.	20
— Number of monitored items, max.	1 000
— Number of server interfaces, max.	2
— Number of nodes for user-defined server interfaces, max.	2 000
<b>Further protocols</b>	
• MODBUS	Yes
<b>communication functions / header</b>	
<b>S7 communication</b>	
• supported	Yes
• as server	Yes
• as client	Yes
• User data per job, max.	See online help (S7 communication, user data size)
<b>Number of connections</b>	
• overall	PG Connections: 4 reserved / 4 max; HMI Connections: 12 reserved / 18 max; S7 Connections: 8 reserved / 14 max; Open User Connections: 8 reserved / 14 max; Web Connections: 2 reserved / 30 max; OPC UA Connections: 0 reserved / 10 max; Total Connections: 34 reserved / 64 max
<b>Test commissioning functions</b>	

<b>Status/control</b>	
<ul style="list-style-type: none"> <li>• Status/control variable</li> <li>• Variables</li> </ul>	Yes inputs/outputs, bit memories, DBs, peripheral I/Os (without fail-safe), times, counters
<b>Forcing</b>	
<ul style="list-style-type: none"> <li>• Forcing</li> </ul>	Yes; peripheral inputs/outputs (without fail-safe)
<b>Diagnostic buffer</b>	
<ul style="list-style-type: none"> <li>• present</li> </ul>	Yes
<b>Traces</b>	
<ul style="list-style-type: none"> <li>• Number of configurable Traces</li> <li>• Memory size per trace, max.</li> </ul>	2 512 kbyte
<b>Interrupts/diagnostics/status information</b>	
<b>Diagnostics indication LED</b>	
<ul style="list-style-type: none"> <li>• RUN/STOP LED</li> <li>• ERROR LED</li> <li>• MAINT LED</li> </ul>	Yes Yes Yes
<b>Integrated Functions</b>	
Frequency measurement	Yes
controlled positioning	Yes
Number of position-controlled positioning axes, max.	8
Number of positioning axes via pulse-direction interface	Up to 4 with SB 1222
PID controller	Yes
Number of alarm inputs	4
<b>Potential separation</b>	
<b>Potential separation digital inputs</b>	
<ul style="list-style-type: none"> <li>• Potential separation digital inputs</li> <li>• between the channels, in groups of</li> </ul>	500V AC for 1 minute 1
<b>Potential separation digital outputs</b>	
<ul style="list-style-type: none"> <li>• Potential separation digital outputs</li> <li>• between the channels</li> <li>• between the channels, in groups of</li> </ul>	Relays No 2
<b>EMC</b>	
<b>Interference immunity against discharge of static electricity</b>	
<ul style="list-style-type: none"> <li>• Interference immunity against discharge of static electricity acc. to IEC 61000-4-2 <ul style="list-style-type: none"> <li>— Test voltage at air discharge</li> <li>— Test voltage at contact discharge</li> </ul> </li> </ul>	Yes 8 kV 6 kV
<b>Interference immunity to cable-borne interference</b>	
<ul style="list-style-type: none"> <li>• Interference immunity on supply lines acc. to IEC 61000-4-4</li> <li>• Interference immunity on signal cables acc. to IEC 61000-4-4</li> </ul>	Yes Yes
<b>Interference immunity against voltage surge</b>	
<ul style="list-style-type: none"> <li>• Interference immunity on supply lines acc. to IEC 61000-4-5</li> </ul>	Yes
<b>Interference immunity against conducted variable disturbance induced by high-frequency fields</b>	
<ul style="list-style-type: none"> <li>• Interference immunity against high-frequency radiation acc. to IEC 61000-4-6</li> </ul>	Yes
<b>Emission of radio interference acc. to EN 55 011</b>	
<ul style="list-style-type: none"> <li>• Limit class A, for use in industrial areas</li> <li>• Limit class B, for use in residential areas</li> </ul>	Yes; Group 1 Yes; When appropriate measures are used to ensure compliance with the limits for Class B according to EN 55011
<b>Degree and class of protection</b>	
IP degree of protection	IP20
<b>Standards, approvals, certificates</b>	
CE mark	Yes
UL approval	Yes
cULus	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes

Marine approval	Yes
<b>Highest safety class achievable in safety mode</b>	
<ul style="list-style-type: none"> <li>• Performance level according to ISO 13849-1</li> <li>• SIL acc. to IEC 61508</li> </ul>	PLe SIL 3
<b>Ambient conditions</b>	
<b>Free fall</b>	
<ul style="list-style-type: none"> <li>• Fall height, max.</li> </ul>	0.3 m; five times, in product package
<b>Ambient temperature during operation</b>	
<ul style="list-style-type: none"> <li>• min.</li> <li>• max.</li> </ul>	0 °C 55 °C; Number of simultaneously activated inputs or outputs 4 or 3 (no adjacent points) at 60 °C horizontal or 50 °C vertical, 8 or 6 at 55 °C horizontal or 45 °C vertical
<ul style="list-style-type: none"> <li>• horizontal installation, min.</li> <li>• horizontal installation, max.</li> <li>• vertical installation, min.</li> <li>• vertical installation, max.</li> </ul>	0 °C 55 °C 0 °C 45 °C
<b>Ambient temperature during storage/transportation</b>	
<ul style="list-style-type: none"> <li>• min.</li> <li>• max.</li> </ul>	-40 °C 70 °C
<b>Air pressure acc. to IEC 60068-2-13</b>	
<ul style="list-style-type: none"> <li>• Operation, min.</li> <li>• Operation, max.</li> <li>• Storage/transport, min.</li> <li>• Storage/transport, max.</li> </ul>	795 hPa 1 080 hPa 660 hPa 1 080 hPa
<b>Altitude during operation relating to sea level</b>	
<ul style="list-style-type: none"> <li>• Installation altitude, min.</li> <li>• Installation altitude, max.</li> </ul>	-1 000 m 5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
<b>Relative humidity</b>	
<ul style="list-style-type: none"> <li>• Operation, max.</li> </ul>	95 %; no condensation
<b>Vibrations</b>	
<ul style="list-style-type: none"> <li>• Vibration resistance during operation acc. to IEC 60068-2-6</li> <li>• Operation, tested according to IEC 60068-2-6</li> </ul>	2 g (m/s <sup>2</sup> ) wall mounting, 1 g (m/s <sup>2</sup> ) DIN rail Yes
<b>Shock testing</b>	
<ul style="list-style-type: none"> <li>• tested according to IEC 60068-2-27</li> </ul>	Yes; IEC 68, Part 2-27 half-sine: strength of the shock 15 g (peak value), duration 11 ms
<b>Pollutant concentrations</b>	
<ul style="list-style-type: none"> <li>• SO2 at RH &lt; 60% without condensation</li> </ul>	SO2: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60% condensation-free
<b>configuration / header</b>	
<b>configuration / programming / header</b>	
<b>Programming language</b>	
<ul style="list-style-type: none"> <li>— LAD</li> <li>— FBD</li> <li>— SCL</li> </ul>	Yes; incl. failsafe Yes; incl. failsafe Yes
<b>Know-how protection</b>	
<ul style="list-style-type: none"> <li>• User program protection/password protection</li> <li>• Copy protection</li> <li>• Block protection</li> </ul>	Yes Yes Yes
<b>Access protection</b>	
<ul style="list-style-type: none"> <li>• protection of confidential configuration data</li> <li>• Protection level: Write protection</li> <li>• Protection level: Read/write protection</li> <li>• Protection level: Complete protection</li> </ul>	Yes Yes Yes Yes
<b>programming / cycle time monitoring / header</b>	
<ul style="list-style-type: none"> <li>• adjustable</li> </ul>	Yes
<b>Dimensions</b>	
Width	110 mm
Height	100 mm
Depth	75 mm
<b>Weights</b>	

---

Weight, approx.

435 g

**last modified:**

4/1/2022 