



S4906WB

Omnidirectional Antenna 4900-5875 MHz

The wide band S4906WB is one in a series of omni antennas that have been optimized for direct chassis mount to outdoor radios or NEMA enclosures. These antennas come standard with an integrated N male or female connector directly mounted to the base of the antenna. The rugged directly mounted connector is perfect for outdoor MESH applications that often require the antenna to be directly mounted to the radio or enclosure. The antenna is enclosed in a UV stable, water-resistant housing and the antenna will provide years of trouble-free service. The antenna series includes antennas of various gains all with integrated N male or female connectors. There is a mast mount hardware kit available for applications that require the antenna to be remotely mounted from the radio enclosure.

FEATURES AND BENEFITS

- Vertically polarized omnidirectional
- Rugged, lightweight, and water resistant
- Direct to radio mounting
- 5 GHz broadband WLAN

APPLICATIONS

- College campuses
- Airports
- Hospitals
- Transportation centers
- WiMAX

ELECTRICAL SPECIFICATION

Model Name	S4906WB
Operating Frequency (MHz)	4900-5875
VSWR - Max	2.0:1
Gain (dBi)	8.0
Nominal Impedance (Ohms)	50
Max Power - Ambient 25°C (W)	10
Polarization	Vertical linear
Vertical Plane 3 dB Beamwidth	16°
Horizontal Plane 3 dB Beamwidth	Omnidirectional



MECHANICAL SPECIFICATION

Dimensions - mm (inches)	292.1 x 25.4 (11.5 x 1.0)
Weight - kg (lbs.)	0.17 (0.37)
Radome Material	White UV polycarbonate
Connector	Type N male female
Mount Style	Direct mount (upright or inverted)

ENVIRONMENTAL SPECIFICATION

Operating Temperature - °C (°F)	-30 to +65°C (-22 to +149°F)
Storage Temperature - °C (°F)	-40 to +80°C (-40 to +176°F)
Wind Operational - km/hr (mph)	161(100)
Wind Survival - km/hr (mph)	219 (136)
Ingress Protection Rating	IP54
Material Substance Compliance	RoHS

RADIATION PATTERNS



TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015

te.com

TE Connectivity, TE Connectivity (logo) and Every Connection Counts are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

TE warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations TE will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the TE product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5) years from the original date of the end product purchase.

©2021 TE Connectivity. All Rights Reserved.

12/21 Original

